




	<a href="#">MAGNET IN A HERMETIC ENCLOSURE OPXM-1 SATEL</a>	<a href="#">WIRELESS RADIATOR THERMOSTAT ART-200 ABAX2 SATEL</a>	<a href="#">CABLE PIN5/RJ-TTL SATEL</a>
			
	37.00 PLN 37.00 PLN	198.00 PLN 198.00 PLN	57.00 PLN 57.00 PLN
Support	AXD-200, XD-2	ABAX2	ETHM-1, VERSA
Length of the cable	...	...	0.3 m
"Index of Protection"	IP65	...	...
Frequency band	...	868 MHz ... 868.6 MHz	...
Radio communication range (at open area)	...	≤ 1000 m	...
Battery	...	2 x LR6 (AA) - 1.5 V (not included)	...
Backup time	...	~ 2 years	...
Current consumption	...	<ul style="list-style-type: none"> <li>• 98 µA (Standby mode)</li> <li>• max. 80 mA</li> </ul>	...

Main features	...	<ul style="list-style-type: none"> <li>• Operation modes : <ul style="list-style-type: none"> <li>- comfortable temperature</li> <li>- economy temperature</li> <li>- manual setting of valve position / temperature</li> </ul> </li> <li>• The temperature can be adjusted within the range : 5 °C ... 30 °C</li> <li>• Remote configuration</li> <li>• View device status</li> <li>• Selection of the temperature sensor to be used - built-in or external (ABAX 2 system)</li> <li>• Boost Heat - quick heating function</li> <li>• Valve descaling function</li> <li>• Open window detection</li> <li>• Child Lock - securing the device against children</li> <li>• Built-in LCD display</li> <li>• Battery charge indicator</li> <li>• battery diagnostics</li> <li>• Bi-directional encrypted radio communication - AES</li> <li>• Transmission channel diversity - automatic selection of the one of 4 channels that will enable transmission without interference with other signals in the 868 MHz frequency band</li> <li>• Remote update of software</li> <li>• The "ECO" option allows to extend the battery life up to four times (only in ABAX2)</li> <li>• Installation on valves : M30 x 1.5 mm</li> <li>• In the kit : <ul style="list-style-type: none"> <li>- Danfoss RA Adapter</li> <li>- positioning ring for easy mounting on smaller diameter valves</li> </ul> </li> </ul>	...
Operation temp	...	-10 °C ... 50 °C	...
Color	White	White	...
Weight	0.05 kg	0.12 kg	0.05 kg
Dimensions	102 x 23 x 20 mm	55 x 102 x 61 mm	...
Manufacturer / Brand	SATEL	SATEL	SATEL
Guarantee	2 years	2 years	2 years