



	<a href="#">AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDBW2241RA-Z-A-27135-S2-DIP - 1080p 2.7 ... 13.5 mm - MOTOZOOM DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, CVBS CAMERA DS-2CE56D8T-IT3ZF(2.7-13.5MM) - 1080p Hikvision</a>
		
	838.00 PLN 838.00 PLN	620.00 PLN 620.00 PLN
Standard	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS
Sensor	Progressive Scan CMOS	Progressive Scan CMOS
Matrix size	2.1 Mpx	2.1 Mpx
Resolution	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
Lens	2.7 ... 13.5 mm - Motozoom - AutoFocus	2.7 ... 13.5 mm - Motozoom
Range of IR illumination	60 m	60 m
View angle	108 ° ... 30 °	<ul style="list-style-type: none"> <li>• 103 ° ... 32 ° (manufacturer data)</li> <li>• 90 ° ... 32 ° (our tests result)</li> </ul>
IR illuminator power adjustment	Automatic	Automatic
Video output	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / CVBS - selectable by switch
S/N ratio	> 65 dB	...
Audio	Microphone built-in - HD-CVI only	...
Main features	<ul style="list-style-type: none"> <li>• Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 8</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• Motozoom lens, AutoFocus</li> <li>• WDR ≥ 130 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 4</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	OSD menu available via DAHUA recorder	✓

Power supply	12 V DC / 580 mA	12 V DC / 620 mA
Power consumption	≤ 6.9 W	≤ 7.5 W
Housing	Dome, Metal	Dome, Metal
Color	White	White
Vandal-proof	IK10	...
"Index of Protection"	IP67	IP67
Supported languages	...	English
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C
Country of origin	...	China
Weight	0.64 kg	0.59 kg
SAP Code	...	300612856
Dimensions	Ø 126 x 100 mm	134 x 111 mm
Manufacturer / Brand	DAHUA	Hikvision
Guarantee	5 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00