

	OVERVOLTAGE LIMITER AXON-VIDEO-IP	WIRELESS TEMPERATURE DETECTOR ATLO-THD2-TUYA Wi-Fi Tuya Smart	WIRELESS TEMPERATURE DETECTOR ATLO-THD1-TUYA Wi-Fi, Tuya Smart
			
	107.45 PLN 107.45 PLN	39.26 PLN 39.26 PLN	73.61 PLN 73.61 PLN
Support	...	Tuya Smart	Tuya Smart
Rated voltage	5 V
Maximal voltage	6 V
Detection	...	Temperature / relative humidity	Temperature / relative humidity
Voltage protection level (line-line)	≤ 40 V
Voltage protection level line-PG	≤ 600 V
Measurement range	...	-10 °C ... 55 °C	-10 °C ... 55 °C
Nominal discharge current (line-line)	100 A (8/20µs)
Nominal discharge current (line-PG)	100 A (8/20µs)
Measurement of humidity	...	0 % ... 99 %	0 % ... 99 %
Maximal discharge current (line-line)	135 A (8/20µs)
Maximal discharge current (line-PG)	135 A (8/20µs)
Capacity	< 20 pF
Alarm signaling	...	Signal to the Tuya Smart mobile application	<ul style="list-style-type: none"> • Buzzer, • Signal to the Tuya Smart mobile application
Protected pairs of wires	1-2, 3-6, 4-5, 7-8
Sockets types	RJ45 (8P8C)
Frequency range	...	2.4 GHz WiFi IEEE 802.11 b/g/n	2.4 GHz WiFi IEEE 802.11 b/g/n
Radio communication range	...	The range limited only by the availability of the Wi-Fi network	The range limited only by the availability of the Wi-Fi network
Mobile phones support	...	It is possible to operate via the Wi-Fi network from the mobile application on the iOS, Android systems : <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	It is possible to operate via the Wi-Fi network from the mobile application on the iOS, Android systems : <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Alarm inputs	—

Power supply	...	2 x 1.5V, type AAA/LR03 battery (included)	<ul style="list-style-type: none"> • 2 x battery LR3 (AAA) 1.5 V (included) • micro USB socket 5 V / 2 A
Current consumption	...	<ul style="list-style-type: none"> ≤ 95 μA - Standby ≤ 135 mA - Alarm signaling 	max. 60 mA
Main features	...	<ul style="list-style-type: none"> • Digital detector • Two programmable temperature thresholds (upper and lower) • Two programmable humidity thresholds (upper and lower) • Selectable measurement unit: °C / °F • Low battery level alarm ≤ 2.4 V • Wall mounting 	<ul style="list-style-type: none"> • LCD display • Digital detector • Signal indicator • Battery charge indicator • Two programmable temperature thresholds (upper and lower) • Two programmable humidity thresholds (upper and lower) • Selectable measurement unit: °C / °F • Low battery level alarm ≤ 2.2 V • Sound signaling : 55 dB • Wall mounting
Color	...	White	White
Manufacturer / Brand	...	ATLO	...
Operation temp	...	-10 °C ... 60 °C	-10 °C ... 60 °C
Permissible relative humidity	...	max. 90 % (non-condensing)	max. 90 % (non-condensing)
Weight	0.05 kg	0.02 kg	0.05 kg
Dimensions	66 x 60 x 30 mm	70 x 25 x 20 mm	Ø 61 x 27 mm
Guarantee	2 years	2 years	2 years