




	<a href="#">DOOR FOR 72-MODULAR DISTRIBUTION CABINETS LE-337253 XL<sup>3</sup> S 160 LEGRAND</a>	<a href="#">OVERVOLTAGE LIMITER LE-412253 THREE-PHASE 1+2 TYPE LEGRAND</a>	<a href="#">BOX FOR FLUSH-MOUNTED CONNECTIONS FOR HOUSEHOLD APPLIANCES PK-AGD/1/EPN Elektro-Plast</a>
			
	55.20 CHF 55.20 CHF	213.55 CHF 213.55 CHF	5.59 CHF 5.59 CHF
Application	Distribution cabinets 3 x 24-modular - XL <sup>3</sup> S 160	...	...
Device type	...	Overvoltage limiter, Three-phase	...
Transparent door	—	...	...
Rated voltage	...	230 / 400 V AC, 50 / 60 Hz	...
Number of terminals	...	...	5 pcs : 2 x 2.5 mm <sup>2</sup> - screw terminals
"Index of Protection"	...	...	IP40
Maximal voltage	...	320 V AC, 50 / 60 Hz	...
Class	...	1+2 type ( Class B+C )	...
Main features	<ul style="list-style-type: none"> <li>• Reversible door</li> <li>• 1 closing point</li> <li>• Supplied with handle in the kit</li> </ul>	...	<ul style="list-style-type: none"> <li>• Claw or screw mounting</li> <li>• Cover fastened with latches</li> <li>• Flat housing profile : 21 mm</li> </ul>
Material	Steel	...	Plastic
Safety class	Grade 2	...	...
Color	White	...	White
Compliance with standards	IEC 60695-2-1	...	...
Protection level Up L/PE, N/PE	...	1.2 kV @ 10/350 μs (T1) 1.7 kV @ 8/20 μs (T2)	...
Nominal discharge current (L/PE, N/PE)	...	8 kA @ 10/350 μs (T1) 20 kA @ 8/20 μs (T2)	...
Maximum stroke current (L/N, L/PE, N/PE)	...	50 kA @ 8/20 μs (T2)	...
Operation state indication	...	✓	...
Connectors type	...	screw terminals	...
Housing	...	Plastic, DIN, TS-35 rail mounting	...
Width in 17.5 mm modules	...	4	...
Weight	3.622 kg	0.552 kg	0.06 kg
Dimensions	547 x 544 x 27 mm	71 x 83 x 70 mm	82 x 82 x 45 mm
Manufacturer / Brand	LEGRAND	LEGRAND	Elektro-Plast Nasielsk
Guarantee	2 years	2 years	2 years