



	SD/MICRO SD MEMORY CARD READER Y-9321 UNITEK	IP CAMERA APTI-AI805VA2-28W-L Full-Color - 8.3 Mpx 4K UHD 2.8 mm
		
	56.80 PLN 56.80 PLN	478.40 PLN 478.40 PLN
Standard	...	TCP/IP
External connector	USB 3.1 - A plug	...
Matrix size	...	8.3 Mpx
Sensor	...	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Supported operating systems	Windows XP/Vista/7/8/8.1/10 (32/64bit), Linux, Mac OS 10.12 or newer	...
Transmission speed	≤ 5 Gb/s	...
Supported memory cards	SD (Secure Digital), microSD - SDHC, SDXC	...
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
Main features	<ul style="list-style-type: none"> • 1 x SD socket • 1 x microSD socket • Reading 2 memory cards simultaneously • Plug & Play 	...
View angle	...	105 °
White light LED illuminator range	...	30 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	25 fps @ 8.3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Memory card slot	...	—
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • External microphone input - Jack 3.5 mm socket • Audio output - Jack 3.5 mm socket • Audio transmission via network • Compliance with the AAC standard
WEB Server	...	Built-in
Max. number of on-line users	...	10
ONVIF	...	19.12

RS-485 interface	...	—
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / admin The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 140 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • ICR - Movable InfraRed filter • Privacy zones • Image rotation and mirror • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of people gathering, loitering detection, motion detection based on human detection uploading face captures to FTP
Power supply	USB	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 450 mA
Power consumption	...	≤ 5.4 W
Housing	...	Dome - Metal

Color	White	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-20 °C ... 60 °C
Weight	0.02 kg	0.5 kg
Dimensions	<ul style="list-style-type: none"> • 38 x 35 x 11 mm • 12 cm (cable length) 	Ø 97 x 91 mm
Supported languages	...	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	UNITEK	APTI
Guarantee	2 years	2 years