



	IP CAMERA IPC-HFW1439TL1-A-IL-BLACK Smart Dual Light - 3.7 Mpx 2.8 mm DAHUA	SMART LIGHT SWITCH ATLO-WB1-TUYA Wi-Fi, Tuya Smart
		
	680.00 PLN 680.00 PLN	48.39 PLN 48.39 PLN
Standard	IP	...
Application	...	Works with lighting - switching on/off
Rated voltage	...	100 ... 240 V AC, 50 / 60 Hz
Maximum power	...	300 W (for each output)
Rated current	...	max. 10 A
Number of buttons	...	1
Number of outputs	...	1
Connector type	...	screw terminals
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Sensor	1/2.9 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	94 °	...
Range of IR illumination	30 m	...
White light LED illuminator range	30 m	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio detection • Compliance with the AAC standard 	...
Main stream frame rate	25 fps @ 3.7 Mpx	...
Operation temp	...	-20 °C ... 50 °C
Interface	10/100 Base-T (RJ-45)	...

Permissible relative humidity	...	≤ 80 %
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Intelligent image analysis	Human detection	...
Main features	<ul style="list-style-type: none"> • When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection - max. 4 configurable zones • Privacy zones - max. 4 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 530 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 6.4 W @ 12 V DC • ≤ 7.7 W @ PoE 	...
Housing	Compact - Metal + Plastic	Plastic
Color	Black	White
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.31 kg	0.09 kg
Dimensions	198 x 80 x 76 mm	87 x 86 x 41 mm



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00