



	IP CAMERA IPC2325LB-ADZK-G - 5 Mpx 2.8 ... 12 mm - MOTOZOOM UNIVIEW	IP SPEED DOME CAMERA OUTDOOR SD4A216DB-HNY WizSense - 1080p 5 ... 80 mm DAHUA
		
	1059.03 PLN 1059.03 PLN	3225.00 PLN 3225.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS	1/2.8 " STARVIS™ CMOS
Matrix size	5 Mpx	2 Mpx
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	2.8 ... 12 mm - Motozoom, AutoFocus	5 ... 80 mm
Optical zoom	...	16x
Digital zoom	...	16x
White light LED illuminator range	...	—
View angle	<ul style="list-style-type: none"> • 109 ° ... 33 ° (manufacturer data) • 101 ° ... 31 ° (our tests result) 	<ul style="list-style-type: none"> • 54 ° ... 4.6 ° (manufacturer data) • 52 ° ... 4.4 ° (our tests result)
Video output	...	—
Range of IR illumination	50 m	100 m
S/N ratio	> 56 dB	...
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 240 °/s (horizontal) • 0.1 °/s ... 160 °/s (vertical)
Preset rotation speed	...	<ul style="list-style-type: none"> • 240 °/s (horizontal) • 160 °/s (vertical)
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-5 ° ... 90 °, Auto Flip - auto-rotates the camera during "tilt" type moving
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	✓
Route settings	...	✓
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	Smart H.265+ / Smart H.264+ / H.265 / H.264 / H.264H / H.264B / MJPEG
Alarm inputs / outputs	—	2 / 1
Main stream frame rate	25 fps @ 5 Mpx	25 fps @ 1080p
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 512GB support (possible local recording)
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection 	<ul style="list-style-type: none"> • Audio input, • Audio output • Bi-directional audio streaming support • Compliance with the AAC standard
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, QoS, IEEE 802.1x, SNMP	...
WEB Server	Built-in	Built-in, NVR compliance
Max. number of on-line users	32	...
ONVIF	✓	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	DHCP or 192.168.1.13	192.168.1.108
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80, 37777
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	37777
Mobile client access ports	80	37777
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette) 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2-DNR, 3-DNR - Digital Noise Reduction • Automatic tracking of moving objects • Day/night mode • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image • Motion Detection • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • SMD 3.0 - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire), entering the marked area, abandoned/missing object, fast moving, parking detection, face detection, detection of people gathering, loitering detection
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 700 mA 	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 2 A (power adapter included)
Power consumption	≤ 8.5 W	<ul style="list-style-type: none"> • ≤ 10 W (typical) • ≤ 19 W (max)
Vandal-proof	—	...
Housing	Compact, Metal	Speed Dome, Plastic
Color	White	White
"Index of Protection"	IP67	IP66
Operation temp	-30 °C ... 60 °C	-40 °C ... 65 °C
Weight	0.55 kg	2.4 kg
Dimensions	206 x 74 x 74 mm	Ø 171 x 170 mm
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Czech, French, Spanish, Dutch, Indonesian (Bahasa), German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	UNIVIEW	DAHUA
Guarantee	3 years	5 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00