







	MEASURING CONNECTOR 2-PIN LSA-W	WIRELESS OPTICAL MOUSE UMY-1077-UGO	ACCESS CONTROLLER MC16-PAC-ST-1-KIT ROGER	ACCESS CONTROL PANEL CPR32-NET-BRD ROGER	POWER DISTRIBUTION UNIT AK-SP-05A AKYGA	DC FILTER FDC-08 TO SWITCHING ADAPTERS
						
	2.60 PLN 2.60 PLN	15.56 PLN 15.56 PLN	1454.96 PLN 1454.96 PLN	1350.05 PLN 1350.05 PLN	37.80 PLN 37.80 PLN	39.97 PLN 39.97 PLN
Maximal current	0.8 A
Number of pins	2 pcs
External connector	...	USB 2.0
Number of served transitions	1 (two-way)
Rated voltage	230 V AC / 50 Hz	...
Number of supported readers	4
Power connectors type	2.1/5/5 mm plug
Total maximal current	10 A	...
Housing type	2.1/5.5 mm socket
Resolution	...	1200 / 1600 / 1800 dpi
Maximal total load	2500 W	...
Inputs	• 8 pcs - Mainboard inputs • max. 32
Number of users	unlimited (purchase of the appropriate license required)
Frequency band	...	2.4 GHz
Response time	< 25 ns	...
Number of outlets	5 grounded outlets 10A/250V	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Supported operating systems	...	Windows XP/Vista/7/8/10, Linux
Buffer memory	8 000 000 events buffer
Automatic delayed fuse	10 A / 250 V	...
Number of access zones	4
Outputs	• 6 pcs - Transistor outputs • 2 pcs - Relay outputs NO/NC
Number of alarm zones	4
Nominal voltage of surge suppressor	250 V / 50 Hz	...
DC filter to eliminate interferences	RFI ≤ 10 dB	...
Events memory	• Events saving to the micro SD card (not included) • Recording up to 240 000 events from the control panel
Maximum stroke current	4.5 kA	...
Maximum energy absorption	150 J	...
Switch	with light indication	...
Communication	• Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface	• 2 x RS-485
Length of the cable	1.8 m	...
Housing	Plastic (ABS)	...
Color	Black	...
Output load	• Transistor outputs : 1 A / 15 V DC • Relay outputs : 1.5 A / 30 V DC

Main features	...	<ul style="list-style-type: none"> • Number of buttons : 6 • Range : 10 m • DPI adjustment • Automatic sleep mode • Plug & Play • The ergonomic shape 	<ul style="list-style-type: none"> • Metal housing • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Central management of the access control system, • Integration with the alarm system SATEL INTEGRA, • History of 250 000 events • Electrical protection of all inputs and outputs as well as communication buses • Full support via network
Power supply	...	2 x 1.5V, type AAA/LR03 battery (not included)	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	<ul style="list-style-type: none"> • 24 V DC • 12 V DC • 18 V AC
Battery backup support	12 V / 20 Ah	✓
Operation temp	5 °C ... 40 °C	5 °C ... 40 °C	5 °C ... 50 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	10 % ... 95 % (non-condensing)
Dimensions	49 x 14 x 9.5 mm	<ul style="list-style-type: none"> • Mouse : 116 x 74 x 39 mm, • Receiver : 14 x 6 x 19 mm 	405 x 365 x 120 mm	175 x 81 x 50 mm	305 x 50 x 40 mm	26 x 21 x 16 mm
Weight	0.003 kg	0.06 kg	3.9 kg	0.15 kg	0.306 kg	0.02 kg
Manufacturer / Brand	...	uGo	ROGER	ROGER	AKYGA	DELTA
Guarantee	...	2 years	3 years	3 years	2 years	3 years