



	CIRCUIT BREAKER HN-C20/1 ONE-PHASE 20 A C TYPE EATON	IP CAMERA IPC2124LB-ADF28KM-H - 3.7 Mpx 2.8 mm UNIVIEW
		
	18.77 PLN 18.77 PLN	642.51 PLN 642.51 PLN
Standard	...	TCP/IP
Device type	Circuit Breaker, One-phase	...
Sensor	...	1/2.9 " Progressive Scan CMOS
Rated current	20 A	...
Matrix size	...	4 Mpx
Number of poles	1	...
Tripping curves	C type	...
Breaking capacity	6000 A	...
Rated voltage	• 230 V AC / 50 Hz • 400 V AC / 50 Hz	...
Connectors type	screw terminals	...
Wire gauge	1 mm ² - 25 mm ²	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
Main features	• Contact position indicator • Possibility of sealing	...
View angle	...	102 °
Range of IR illumination	...	30 m
Width in 17.5 mm modules	1	...
S/N ratio	...	> 52 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in, • Audio transmission via network, • Audio detection
Main stream frame rate	...	20 fps @ 4 Mpx 25 fps @ 3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓

Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA
Power consumption	...	≤ 5.5 W
Housing	Plastic, DIN, TS-35 rail mounting	Compact, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C

Weight	0.100 kg	0.38 kg
Dimensions	85 x 73 x 17.5 mm	166 x 63 x 62 mm
Supported languages	...	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	EATON	UNIVIEW
Guarantee	2 years	3 years