





	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V2-28 2Mpx / 5Mpx 2.8 mm	PANEL WITH CABLE ENTRY A19-PK-V1	CONNECTOR WITH ELASTIC SEALING F/6.8*P10	PLUG F/7.0*P10
				
	124.80 PLN 124.80 PLN	22.40 PLN 22.40 PLN	7.49 PLN 7.49 PLN	7.68 PLN 7.68 PLN
Width	...	19 "
Height	...	1 U
Material	...	Steel - powder painted
Standard	AHD, HD-CVI, HD-TVI
In package	10 pcs The price for package	10 pcs The price for package
Sensor	1/3 " Progressive Scan CMOS
Connector type	"F" Straight plug	"F" Straight plug
Matrix size	5 Mpx
Attachment of connector elements	Twisted-on	Twisted-on
Shield fastening	Twisting-on	Twisting-on
Wire mounting	—	—
Application	...	RACK 19"	Coaxial cable	Coaxial cable
Cable diameter	max. 6.8 ± 0.05 mm	max. 7.0 mm
Impedance	75 Ω	75 Ω
Material	Metal	Metal
Example of application	• HFEK • Triset113
Main features	...	<ul style="list-style-type: none"> • Dimensions of the cable entry hole : 431 x 27 mm (full frame) • 4-point fixing to the front RACK rails • 4 pcs. of M6 screws with cage nuts included • Corrosion resistance 	<ul style="list-style-type: none"> • Elastic sealing • Wide frequency range • Corrosion resistance 	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • Elastic sealing
Resolution	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination	20 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm
View angle	• 89 ° (manufacturer data) • 83 ° (our tests result)

Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu	✓
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only
Housing	Dome - Metal
Color	Graphite	Black (RAL 9005)
Vandal-proof	—
"Index of Protection"	IP67
Power supply	12 V DC / 230 mA
Power consumption	≤ 2.8 W
Operation temp	-20 °C ... 60 °C
Weight	0.42 kg	0.25 kg	0.003 kg	0.005 kg
Dimensions	Ø 96 x 91 mm	483 x 44 x 12 mm	Ø 11 mm x 20 mm	Ø 11 mm x 17 mm
Supported languages	Polish, English
Manufacturer / Brand	APTI
Guarantee	2 years	2 years	2 years	2 years