






	COAXIAL CABLE CTF-113/ZEL	TV OR MONITOR MOUNT BRATECK-LCD-142A	TV OR MONITOR MOUNT AX-HAMMER	TV OR MONITOR MOUNT AX-TYTAN-MAXXIM	CONNECTOR STRIP KE-224-112/WAGO
					
	2.52 PLN 2.52 PLN	66.00 PLN 66.00 PLN	114.35 PLN 114.35 PLN	98.90 PLN 98.90 PLN	0.66 PLN 0.66 PLN
Number of terminal pairs	1
Connector type	3 x spring terminal - 2 x Wire + 1 x Stranded wire
In section	100 m . Price for 1m when buying a whole roll
Coaxial cable	CTF 113
Inner conductor	Ø 1.13 mm Cu Wire
Mounting standard	...	VESA 75, 100, 150, 200, 200x100	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	...
Dielectric	Ø 4.8 mm PE (physical foam)
Wire gauge	• 1.0 ... 2.5 mm ² - Wire, • 0.5 ... 2.5 mm ² - Stranded wire
Screen size range	...	17 " ... 37 "	23 " ... 70 "	36 " ... 70 "	...
Nominal voltage	400 V
Bearing capacity	...	20 kg	50 kg	50 kg	...
Shield	Foil Al/PET/Al - Gel-filled
Rated current	24 A
Braid	Al wire
Distance from mounting surface	...	70 ... 250 mm from wall	83 ... 455 mm	75 ... 400 mm	...
Braid density	90 %
Color	...	Black	Black	Black	White
Outer coating	Ø 7 mm PE
Coating color	Black
Tilt adjustment	...	-15 ° ... 15 °	0 ° ... 15 °	0 ° ... 10 °	...
Impedance	75 Ω ± 3 Ω
Manufacturer / Brand	WAGO
Horizontal rotation	...	Articulated arm with two swivels in range -90 ° ... 90 ° each	-45 ° ... 45 °	-90 ° ... 90 °	...
Capacity	52 pF/m
Rotation in the plane of the screen	...	360 °	—	± 3 °	...
Resistance of the inner conductor for DC current	17 Ω/km
Screening efficiency	> 90 dB
Return loss	28 dB @300MHz 26 dB @900MHz 23 dB @2150MHz
Shortening wave coefficient	85 %
Dimensions	...	195 x 119 x (70 ... 250) mm	670 x 430 x (83 ... 455) mm	640 x 420 x (75 ... 400) mm	20.5 x 15.5 x 9.5 mm
Weight	38.4 kg/km	1.1 kg	4.8 kg	4.52 kg	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Cable attenuation at 100m section	3.9 dB @ 50 MHz 7.8 dB @ 200 MHz 12.3 dB @ 450 MHz 17 dB @ 860 MHz 18.6 dB @ 1000 MHz 21.9 dB @ 1350 MHz 25.2 dB @ 1750 MHz 28.2 dB @ 2150 MHz 33.8 dB @ 3000 MHz
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00