



	POLE MOUNT DS-1475ZJ-SUS Hikvision	ACCESS POINT RG-AP680(CD) Wi-Fi 6, SFP 2.4 GHz, 5 GHz, 547 Mbps + 1201 Mbps RUIJIE
		
	229.00 PLN 229.00 PLN	2485.00 PLN 2485.00 PLN
Suitable for cameras	Hikvision	...
Pole diameters range	Ø 67 ... Ø 127 mm	...
Material	Stainless steel	...
Color	White	...
SAP Code	302701860	...
Frequency range	...	<ul style="list-style-type: none"> • 2.4 GHz (2.4 ... 2.4835 GHz), • 5 GHz (5.150 ... 5.250, 5.250 ... 5.350, 5.470 ... 5.725, 5.725 ... 5.850 GHz)
Antenna type	...	<ul style="list-style-type: none"> • 2x2 MU-MIMO - embedded • 9 dBi @ 2.4 GHz • 9 dBi @ 5 GHz
Standards	...	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n/ax @ 2.4 GHz, • IEEE 802.11 a/n/ac/ax @ 5 GHz
Baud rates	...	547 Mbps @ 2.4 GHz + 1201 Mbps @ 5 GHz
LAN ports	...	<ul style="list-style-type: none"> • 1 x 10 / 100 / 1000 Mbps Ethernet + PoE IN - RJ45, • 1 x 1000 Mbps - SFP
Port USB	...	—
LED indicators	...	Power / System, 3 x Signal indicator
DDNS	...	—
DHCP server	...	✓
Firmware update	...	✓

Protections	...	<ul style="list-style-type: none"> • WEP 64/128-bit, WPA-TKIP, WPA-PSK, WPA2 AES • IEEE 802.1x and Radius Authentication • Black list • Access Control List - ACL package filtering based on source and destination MAC addresses • CPP • NFPP • SSID hiding
Operation modes	...	Access Point
Management interface	...	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reye application • Remote management • Web browser • Console - RJ-45 output
Mobile phones support	...	Android: Free application Ruijie Reye iOS (iPhone): Free application Ruijie Reye
Default IP address	...	192.168.110.1
Transmitter power	...	max. 28 dBm @ 2.4 GHz max. 28 dBm @ 5 GHz



Main features	...	<ul style="list-style-type: none"> • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • OFDMA • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Load balance • WLAN : 32 x BSSID • Multicast • IPv4/IPv6 • ICMP - Static routing • VPN support : IPsec, PPPoE • SNMP • Statistical Reporting, System logs • DHCP client • Bluetooth 5.0 interface • RESET button • Signal indicator • Industrial wide temperature design. • Overvoltage protection : 9 kV
Housing	...	Plastic, hermetic
"Index of Protection"	...	IP68
Power supply PoE	...	PoE (802.3af/at)
Power supply	...	<ul style="list-style-type: none"> • 48 V DC / 0.35 A (not included) • PoE / PoE+
Power consumption	...	max. 12.95 W
Operation temp	...	-40 °C ... 65 °C
Permissible relative humidity	...	0 % ... 100 % (non-condensing)
Weight	1.23 kg	• 1.2 kg (without bracket)
Dimensions	127 x 250 x 46 mm	251 x 168 x 64 mm (without bracket)
Manufacturer / Brand	Hikvision	RUIJIE
Guarantee	3 years	3 years