



	MOUNT RACK FRAME U19-4U/340	ACCESS CONTROLLER ASC2202B-D DAHUA
		
	99.49 PLN 99.49 PLN	1109.00 PLN 1109.00 PLN
Number of served transitions	...	2 (two-way)
Color	Black (RAL 9005)	...
Support	...	DAHUA
Number of supported readers	...	4 pcs
Internal depth	330 mm	...
Battery backup support	...	—
Output lines	...	4 pcs - Relay
Communication	...	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1.4 A
Main features	...	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail
Default IP address	...	192.168.0.2
Default admin user / password	...	admin / - The administrator password should be set at the first start

Operation temp	...	-30 °C ... 60 °C
Permissible relative humidity	...	max. 95 % (non-condensing)
Weight	2.71 kg	0.4 kg
Dimensions	500 x 151 x 331 mm - RACK 19 " x 4 U	210 x 106 x 50 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years