


	IP CAMERA DS-2CD2T47G2-L(2.8MM)(C)(BLACK) ColorVu - 4 Mpx Hikvision	STYROFOAM PLUG SM-95/EPN*P4 Elektro-Plast
		
	1773.00 PLN 1773.00 PLN	8.41 PLN 8.41 PLN
Standard	TCP/IP	...
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
In package	...	4 pcs The price for package
Length	...	95.5 mm
Diameter	...	Ø 20 mm / Ø 24 mm
Thickness of the Styrofoam	...	≥ 100 mm
Diameter of the screw	...	Ø 4 mm ... Ø 5 mm
Resolution	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm, F1.0	...
View angle	• 109 ° (manufacturer data) • 101 ° (our tests result)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
White light LED illuminator range	60 m	...
Alarm inputs / outputs	—	...
Audio	—	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in, NVR compliance	...
Max. number of on-line users	6	...
ONVIF	18.12	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect	...
Default admin user / password	admin / -	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
RS-485 interface	—	...
Main features	<ul style="list-style-type: none"> • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles • Possibility to turn off the LED illuminator • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, scene changing, face detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 710 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 10.5 W @ PoE (802.3af) • ≤ 8.5 W @ 12 V DC 	...
Housing	Compact, Aluminum	...
Color	Black	...
"Index of Protection"	IP67	...
Weight	1.1 kg	0.01 kg / 1 pcs
Dimensions	Ø 105 x 290 mm	...
Operation temp	-30 °C ... 60 °C	...
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	Elektro-Plast Nasielsk
SAP Code	311323805	...
Guarantee	3 years	2 years