



	INDUSTRIAL POE SWITCH TSW200 8-PORT SFP Teltonika	SWITCH POE IP-8-20-H 8- PORT ATTE
		
	305.30 PLN 305.30 PLN	1259.00 PLN 1259.00 PLN
LAN ports	<ul style="list-style-type: none"> • 8 RJ45 (8 x PoE+ (802.3af/at)), • 2 x SFP (Uplink) 	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-TX - Uplink • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE
Management	—	—
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 1000 Mbps - 2 SFP (Uplink) ports 	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports • 10 / 100 / 1000 Mbps : 2 Port LAN
LED diodes	Power, Link/Act, SFP	Power, LAN
MAC addresses table	2k	...
Maximal output power	30 W / port PoE - 1 ... 8 ports	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports
Maximal total power	240 W	96 W
Certificates	CE, UKCA, FCC	...
Housing	Aluminum	...

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • Mounting on DIN rail, • 2-pin industrial power socket, • Wide range of supported supply voltages • Grounding • "Index of Protection" : IP30 	<ul style="list-style-type: none"> • Pin numbers for RJ-45 connector : 1/2, 3/6 - Wires to data transmission ; 4/5, 7/8 - Power supply • Possibility to connecting in cascade • Efficiency : 92 % @ 90 W • Built-in switching power supply : 48 V DC / 96 W • PSU thermal protection • Short-circuit protection • Overload protection • TAMPER switch indicating open the cover • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • Electronic fuse independently for each PoE channel • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • Main cable entries on the back of the enclosure • "Index of Protection" : IP20
Power supply	<ul style="list-style-type: none"> • 7 ... 57 V DC (power adapter not included), • 44 ... 57 V DC - PoE IN 	180 ... 240 V AC - Built-in switching power supply
Power consumption	<ul style="list-style-type: none"> • max. 5.5 W • PoE max. 245.5 W 	...
Operation temp	-40 °C ... 75 °C	...
Weight	0.51 kg	4.33 kg
Dimensions	132 x 44 x 95 mm	400 x 450 x 140 mm
Manufacturer / Brand	Teltonika	ATTE
Guarantee	2 years	3 years