



	CEE-CONNECTOR PCE-2246 400 V 32 A 4P 6H IP44 / IP54	NVR NVR501-08B-LP8 8 CHANNELS, 8 PoE UNIVIEW
		
	28.72 PLN 28.72 PLN	1617.51 PLN 1617.51 PLN
Standard	...	TCP/IP
Rated voltage	400 V / 50 ... 60 Hz	...
Supported resolutions	...	max. 8.3 Mpx 4K UHD - 3840 x 2160 px
Maximal current load	32 A	...
Number of poles	4P	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Grounding	6h	...
Electrical cable	max. 4 x 6 mm ²	...
Cable terminals	screw terminals	...
Audio support	...	<ul style="list-style-type: none"> • 8 Channels - Audio from cameras • Bi-directional audio streaming support
Plug type	CEE	...
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
"Index of Protection"	IP44 / IP54	...
Contact material	CuZn	...
Maximum wire insulation diameter	20 mm	...
Image compression method	...	Ultra 265 / H.265 / H.264
Bitrate	...	max. 80 Mbps
Supported hard drives	...	1 x 6 TB SATA
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Color	Red	...
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback
Network interface	...	1 x RJ-45 10/100 Base-TX

Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Network protocols	...	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, RTSP
ONVIF	...	✓
Default IP address	...	DHCP or 192.168.1.30
Default admin user / password	...	admin / 123456
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
RTSP URL	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	...	1 x USB 2.0 1 x USB 3.0
Serial ports	...	—
Alarm inputs / outputs	...	—
PTZ control	...	PTZ Uniview cameras
Motion Detection	...	✓
Intelligent image analysis	...	✓

Main features	...	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, scene changing, abandoned/missing object, objects tracking, people counting, crowd gathering estimation • Human detection • Audio detection • Support ANR function • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	8-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)
Maximum total switch load	...	75 W
Power supply	...	52 V DC / 1.8 A (power adapter included)
Power consumption	...	max. 10 W (without HDD)
Operation temp	...	-10 °C ... 55 °C
Weight	0.25 kg	0.71 kg
Dimensions	161 x 94 x 67 mm	270 x 212 x 46 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	PCE	UNIVIEW
Guarantee	2 years	3 years