



	NVR APTI-N0911-I3 9 CHANNELS	NVR BCS-B-NVR0801-8P(2.0) 8 CHANNELS, 8 PoE BCS BASIC
		
	206.40 PLN 206.40 PLN	565.00 PLN 565.00 PLN
Standard	TCP/IP	TCP/IP
Supported resolutions	max. 8 Mpx - 3840 x 2160 px, 4K UHD	max. 8 Mpx 4K UHD - 3840 x 2160 px
Video outputs	1 pcs HDMI 4K 1 pcs VGA	1 pcs HDMI 4K 1 pcs VGA
Audio support	<ul style="list-style-type: none"> • 9 Channels - Audio from cameras • Bi-directional audio streaming support 	8 Channels - Audio from cameras
Audio inputs	1 pcs CINCH	—
Audio outputs	1 pcs CINCH	1 pcs CINCH
Image compression method	H.265+ / H.265 / H.264+ / H.264	H.265+ / H.265 / H.264+ / H.264
Bitrate	80 Mbps	max. 50 Mbps
Supported hard drives	1 x 8 TB SATA	1 x 6 TB SATA
Recording modes	Manual, Motion Detection, Schedule	Manual, Motion Detection, Schedule
External storage devices backup	Records backup at (.avi) format to USB (pendrive)	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast Playback max. 4 cameras in the same time @ 1080p	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/9 channel synchronous playback
Network interface	1 x RJ-45 10/100 Base-TX	1 x RJ-45 10/100/1000 Base-TX
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Mobile client access ports	...	80
Network protocols	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE	P2P, UPnP, DHCP

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

ONVIF	✓	✓
Default IP address	192.168.1.88	DHCP or 192.168.1.30
Default admin user / password	admin / 12345	admin / 123456
RTSP URL	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
Mobile phones support	Access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • Android: Free application BitVision , iOS: Free application iVMS320	Port no.: 80 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Web browser access ports	80, 5000, 554	80, 554
PC client access ports	80, 5000, 554	Port no.: 80 or access by a cloud (P2P)
Maximum total switch load	...	75 W
USB	2 pcs USB 2.0	2 x USB 2.0
Serial ports	—	...
Alarm inputs / outputs	—	—
PTZ control	IP Speed Dome Cameras	IP Speed Dome Cameras
Motion Detection	Split the screen into zones : 22 x 18 motion zones	✓
Intelligent image analysis	✓	...
Main features	• Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom	...
Mouse support	✓	✓
IR remote controller in the set	—	—
Switch PoE	—	8-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)
Power supply	12 V DC / 2 A (power adapter included)	52 V DC / 1.8 A (power adapter included)
Power consumption	≤ 10 W (without HDD)	max. 9 W (without HDD)
Operation temp	-10 °C ... 50 °C	...
Weight	0.85 kg	0.97 kg
Dimensions	260 x 237 x 45 mm	260 x 243 x 46 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	APTI	BCS BASIC
Guarantee	2 years	3 years