



	IP VANDALPROOF CAMERA IPC-HDBW5449R-ASE-NI-0360B Full-Color - 4 Mpx 3.6 mm DAHUA	MAST CAP ZM-35/40
		
	2122.00 PLN 2122.00 PLN	1.20 PLN 1.20 PLN
Standard	TCP/IP	...
Hole diameter	...	Ø 35 ... Ø 39 mm
Sensor	1/1.8 " Progressive Scan CMOS	...
Material	...	PET
Matrix size	4 Mpx	...
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	3.6 mm	...
View angle	<ul style="list-style-type: none"> • 93 ° (manufacturer data) • 88 ° (our tests result) 	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection 	...
Bitrate	32 ... 8192 kbps - H.264 19 ... 8192 kbps - H.265	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, IEEE 802.1x, SNMP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	18.06	...

Main features	<ul style="list-style-type: none"> • WDR - 140 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Heat map - the selection in the image by corresponding colors the areas with different traffic • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, fast moving, loitering detection, illegal parking, detection of people gathering, people counting - detection and maintenance of 4 independent areas, abandoned/missing object, scene changing, face detection 	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.108	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • ePoE, • 12 V DC / 370 mA 	...
Power consumption	≤ 4.4 W	...
Housing	Dome - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.45 kg	0.006 kg
Dimensions	Ø 122 x 90 mm	Ø 40 x 20 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Italian	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00