




	FLUSH-MOUNTING DISTRIBUTION CABINET 24-MODULAR ELEGANT-2X12/PT/W/EPN Elektro-Plast	DUAL SMART LIGHT SWITCH ATLO-WB2-TUYA Wi-Fi, Tuya Smart	EXTENDER ETHERNET+PoE LR1002-1ET-V3 TRANSMITTER DAHUA
			
	84.73 PLN 84.73 PLN	43.43 PLN 43.43 PLN	110.00 PLN 110.00 PLN
Method of mounting	Flush-mounted
LAN ports	1 pcs RJ45
Application	...	Works with lighting - switching on/off	...
Transmission ports	1 pcs BNC
Number of mounted modules	12 x 2 rows, 17.5 mm
Transmission speed	10 / 100 Mbps
Spacing between TH 35 rails	150 mm
Rated voltage	...	100 ... 240 V AC, 50 / 60 Hz	...
Transparent door	✓
Maximum power	...	300 W (for each output)	...
Rated current	...	max. 10 A	...
Transmission range	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver
Number of buttons	...	2	...
Protections	Overvoltage
Number of outputs	...	2	...
Connector type	...	screw terminals	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...

Equipment	Terminal blocks : • Double-row terminal block - 2 x N : 6 x 10 mm ² + 8 x 16 mm ² • 1 pcs PE : 6 x 10 mm ² + 8 x 16 mm ²
Mobile phones support	...	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS	...
Material	Plastic
"Index of Protection"	IP40
IK rating	—
Power supply	• ePoE • PoE (802.3af/at)
Compliance with standards	IEC/EN 62208, IEC/EN 60670-24
Manufacturer / Brand	Elektro-Plast Nasielsk	...	DAHUA
Main features	• Removable chassis with TH 35 rails	• Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication	• Plug & Play • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Support for IP cameras and network devices • Easy installation - doesn't require any configuration of IP nor MAC address • Power supply PoE - pins 1, 2 and 3, 6 • The device operates from the camera side • Possibility to mount on a wall, or on the DIN TS-35 rail • UTP cable length to the camera max. 2 m
Housing	...	Plastic	...
Color	White	White	...
Operation temp	...	-20 °C ... 50 °C	...
Permissible relative humidity	...	≤ 80 %	...
Weight	1.26 kg	0.098 kg	0.07 kg
Dimensions	407 x 303 x 102 mm	87 x 86 x 41 mm	79 x 64 x 23 mm
Guarantee	2 years	2 years	3 years