

	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTL-AI80FQRTD 4.5 mm - 1080p	TOOL FOR CLEANING FIBER OPTIC CONNECTORS WUN-XK25 SC-APC / SC-UPC	HOUSING A19-TS-35/OB-3U/160	PANEL WITH CABLE ENTRY A19-PK
				
	180.00 PLN 180.00 PLN	31.12 PLN 31.12 PLN	314.00 PLN 314.00 PLN	31.50 PLN 31.50 PLN
Application	...	Ideal for removing dirt from optical components
Width	19 "	19 "
Height	3 U	1 U
Connector type	...	SC-APC / SC-UPC
Material	Steel - powder painted	Steel - powder painted
Scanning system	Progressive
Application	RACK 19"	RACK 19"
Optical zoom	—
Sensor	1/2.9 " GC2093 1/2.9 " GC2053
Matrix size	2.1 Mpx 2 Mpx
Lens	4.5 mm 4.5 mm
Main features	<ul style="list-style-type: none"> • TH-35 rail • Corrosion resistance • Possibility to mount of 24 fuses, 1 S wide • 6-point fixing to the front RACK rails • 6 pcs. of M6 screws with cage nuts included • The enclosure features labeling field 420x20 mm • 10 rubber bushings in the top and bottom part of the enclosure • Mounting plate for a 7Ah/12V battery included 	<ul style="list-style-type: none"> • 389 x 30 mm (opening for cables entry) • Cable entry with brushes ensuring protection against dust • 4-point fixing to the front RACK rails • 4 pcs. of M6 screws with cage nuts included • Corrosion resistance
Operation temp	-10 °C ... 40 °C	...
Cards support	13.56 MHz S50
Keyboard built-in	—
Doorbell button	—
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 640 x 480 px
View angle	66 ° 66 ° 90 °
Interface	USB, RS-232 TTL

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximum background illumination	100 000 Lux
QR codes reading	<ul style="list-style-type: none"> • 1D : EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5 (ITF), ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5 • 2D : QR Code, Data Matrix, PDF417, Aztec
Reading distance	<ul style="list-style-type: none"> • EAN13 (13 mm) : 30 ... 140 mm • Code 39 (5 mm) : 30 ... 50 mm • QR Code (20 mm) : 35 ... 120 mm • Data Matrix (10 mm) : 30 ... 70 mm • PDF417 (6.67 mm) : 30 ... 80 mm
Minimal contrast	25 %
Standard	TCP/IP
Range of IR illumination	5 m
White light LED illuminator range	5 m
Temperature measurement	✓
Temperature measurement range	35.7 °C ... 42 °C
Accuracy of temperature measurement	± 0.3 °C
Temperature measurement distance	0.7 m ... 1.2 m
Face recognition distance	0.5 m ... 2.0 m (max 30 000 faces in the database)
Internal memory	Support storage of 50 000 records
Video output	—
RS-485 interface	✓
Wiegand interface	✓
Memory card slot	—
Alarm inputs / outputs	0 / 1
Audio	Speaker built-in
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4, TCP/IP, HTTP, MQTT, RTSP, SMTP, NTP
WEB Server	Built-in
ONVIF	—
Default IP address	DHCP / 192.168.1.88
Default admin user / password	admin / 12345
Web browser access ports	80

PC client access ports	80
Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 800 x 1280 px, 8 " • Wiegand 34/26 • Day/Night mode (color/b&w/auto) • RESET button • Alarm output of NO/NC relay type • Relay output operating modes: access control or notification of an exception • Built-in QR code reader
Power supply	12 V / 2 A DC
Power consumption	≤ 18 W
Housing	Compact - Metal
Color	Silver	...	Black (RAL 9005)	Black (RAL 9005)
"Index of Protection"	—	...	IP20	...
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)
Weight	1.8 kg	0.02 kg	3.3 kg	0.225 kg
Dimensions	366 x 132 x 144 mm	178 x 17 x 17 mm	445 x 125 x 155 mm Internal dimensions 481.5 x 132 x 234 mm External dimensions	483 x 44 x 15 mm
Montage hole diameter	35 mm
Length of the cable	65 cm
Supported languages	English, French, Spanish, Ukrainian, Italian
Manufacturer / Brand	APTI	...	PULSAR	...
Guarantee	3 years	...	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00