



	<a href="#">UNIVERSAL CLEANING WIPES UNI-WIPES/24 AG TERMOPASTY</a>	<a href="#">IP CAMERA BCS-L-TIP55VSR6-AI1-G - 5 Mpx 2.7 ... 13.5 mm - MOTOZOOM BCS Line</a>
		
	4.05 PLN 4.05 PLN	1899.00 PLN 1899.00 PLN
Application	Wet wipes for the care of office equipment	...
Standard	...	TCP/IP
Sensor	...	1/2.7 " Progressive Scan CMOS
Wipe dimensions	220 x 160 mm	...
Matrix size	...	5 Mpx
Packaging	24 wipes	...
Resolution	...	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	...	2.7 ... 13.5 mm - Motozoom
View angle	...	• 99 ° ... 28 ° (manufacturer data) • 106 ° ... 34 ° (our tests result)
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding
Range of IR illumination	...	60 m
Alarm inputs / outputs	...	1 / 1
Main stream frame rate	...	• 20 fps - 5 Mpx • 25 fps - 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP
Audio	...	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
WEB Server	...	Built-in
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Max. number of on-line users	...	20
ONVIF	...	✓
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">BCS Manager</a> • iOS (iPhone): Free application <a href="#">BCS Manager</a>
Default IP address	...	192.168.1.108

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&amp;subtype=0</li> <li>• Sub stream : rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&amp;subtype=1</li> </ul>
RS-485 interface	...	—
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Mirror - Mirror image</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Sharpness - sharper image outlines</li> <li>• Configurable Privacy Zones</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), Smart motion detection (with recognizing people and vehicles)</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 820 mA</li> </ul>
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 8.5 W @ PoE (802.3at)</li> <li>• ≤ 7.4 W @ 12 V DC</li> </ul>
Housing	...	Compact, Metal
Color	...	Black
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Supported languages	...	Polish, English
Weight	...	0.74 kg
Dimensions	...	244 x 79 x 76 mm
Manufacturer / Brand	AG TERMOPASTY	BCS Line
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00