



	<a href="#">SWITCH POE GTX-A1-06-42-V2 4-PORT</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16H8T-IT3F(2.8mm) - 5 Mpx Hikvision</a>
		
	136.00 PLN 136.00 PLN	489.00 PLN 489.00 PLN
Standard	...	AHD / HD-CVI / HD-TVI / CVBS
Sensor	...	Progressive Scan CMOS
Matrix size	...	5.0 Mpx
LAN ports	<ul style="list-style-type: none"> <li>• 4 x RJ45 10/100 Base-T ( 4 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100 Base-T - Uplink</li> </ul>	...
Management	—	...
LED diodes	Power, S - Extend, PoE, Link/Act	...
Transmission speed	10 / 100 Mbps : 4 LAN & PoE ports + 2 Uplink ports	...
Maximal output power	30 W / port PoE 802.3af/at - 1 ... 4 ports	...
Maximal total power	60 W	...
Operation modes	<ul style="list-style-type: none"> <li>• N - Normal - the device operates as normal PoE switch</li> <li>• S - Extend - Range : 250 m @ 10 Mbps</li> </ul>	...
Resolution	...	<ul style="list-style-type: none"> <li>• AHD / HD-TVI : 2560 x 1944 - 5 Mpx ,</li> <li>• AHD / HD-CVI / HD-TVI : 2560 x 1440 - 4 Mpx ,</li> <li>• HD-TVI : 1920 x 1080 - 1080p ,</li> <li>• CVBS : 960 x 576 - 960H</li> </ul>
Lens	...	2.8 mm
Certificates	CE	...
View angle	...	<ul style="list-style-type: none"> <li>• 98 ° (manufacturer data)</li> <li>• 95 ° (our tests result)</li> </ul>
Range of IR illumination	...	60 m
IR illuminator power adjustment	...	Automatic

Operation temp	-10 °C ... 55 °C	...
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / CVBS, BNC socket
OSD menu	...	OSD menu available via recorder
Main features	...	<ul style="list-style-type: none"> <li>• WDR ≥ 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• BLC - Back Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	100 ... 265 V AC	12 V DC / 480 mA
Power consumption	...	≤ 5.8 W
Housing	Desktop, Metal	Compact, Metal + Plastic
Color	...	White + Black
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	0.49 kg	0.57 kg
Dimensions	145 x 100 x 32 mm	217 x 87 x 80 mm
Supported languages	...	English
Manufacturer / Brand	...	Hikvision
SAP Code	...	300510468
Guarantee	2 years	3 years