



	SWITCH POE IP-5-11-M2 5-PORT ATTE	INSULATION STRIPPER HT-332
		
	475.00 PLN 475.00 PLN	12.78 PLN 12.78 PLN
Material	...	PET
Application	...	Coaxial cable RG58 RG59 RG6
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	...
Management	—	...
LED diodes	Power, LAN	...
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	...
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	...
Maximal total power	96 W	...
Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 • Port LAN 6 - Uplink 	...

Main features	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement 	Left shield width adjustment
Power supply	230 V AC - cable terminals	...
Weight	0.65 kg	...
Dimensions	226 x 148 x 80 mm	...
Manufacturer / Brand	ATTE	...
Guarantee	3 years	2 years