



	EXTENDER EXT-POE2 PULSAR	EXTENDER EXT-POE4H IN A HERMETIC CASING PULSAR
		
	124.00 PLN 124.00 PLN	174.00 PLN 174.00 PLN
Standards	PoE : IEEE 802.3at, IEEE 802.3af	...
Input voltage	42 ... 57 V DC	42 ... 57 V DC
Output voltage	42 ... 57 V DC	42 ... 57 V DC
Number of inputs	1	1
Number of outputs	2	2
Connector	3 x RJ-45 socket	3 x RJ-45 socket
LED indicators	Link/Act	Link/Act
Supported data rates	<ul style="list-style-type: none"> • Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates : 10 / 100 Mbps - Fast Ethernet 	<ul style="list-style-type: none"> • Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet
Output power	max. 15.4 W / port PoE max. 20 W (total)	max. 14.4 W / port PoE , max. 20 W (total)
Protections	<ul style="list-style-type: none"> • Overvoltage • Overload • Short-circuit 	<ul style="list-style-type: none"> • Overvoltage • Overload • Short-circuit
Housing	Metal	Plastic, hermetic
"Index of Protection"	...	IP56
Operation temp. / Relative humidity	-10 ... 40 °C / 10 ... 90 %	-10 ... 40 °C / 10 ... 90 %
Weight	0.11 kg	0.55 kg
Dimensions	81 x 77 x 26 mm	198 x 148 x 80 mm
Manufacturer / Brand	PULSAR	PULSAR
Guarantee	2 years	2 years