



	<a href="#">NVR TC-R3440 SPEC:1/B/N/V4.0 40 CHANNELS TIANDY</a>	<a href="#">ACCESS POINT +ROUTER ACB-AC Wi-Fi 5, 5 GHz, 2.4 GHz, 867 Mbps + 300 Mbps UBIQUITI</a>
		
	4200.00 PLN 4200.00 PLN	409.89 PLN 409.89 PLN
Standard	IP	...
Supported resolutions	max. 16 Mpx	...
Frequency range	...	5 GHz , 2.4 GHz ,
Video outputs	1 pcs HDMI 4K 1 pcs VGA Video outputs are independent of each other	...
Audio support	40 Channels - Audio from cameras	...
Audio inputs	1 pcs	...
Audio outputs	1 pcs	...
Antenna type	...	2x2 MIMO - built-in • 4 dBi @ 2.4 GHz • 5 dBi @ 5 GHz
Image compression method	S+265 / H.265 / S+264 / H.264	...
Standards	...	IEEE 802.11ac, Wi-Fi 5
Supported hard drives	4 x 10 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Baud rates	...	867 Mbps @ 5 GHz + 300 Mbps @ 2.4 GHz
Protections	...	WPA2
Searching and playback the records	<ul style="list-style-type: none"> <li>Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>Advanced searching (to the one second accuracy)</li> <li>Playback max. 16 cameras in the same time</li> </ul>	...
LAN ports	...	4 x 10/100/1000 Mbps
Transmitter power	...	22 dBm (max)
Power supply PoE	...	Ubiquiti Passive PoE
Power consumption	...	≤ 8.5 W
Network interface	2 x RJ-45 - 10 / 100 / 1000 Mbps	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...

ONVIF	✓	...
Bitrate	max. 400 Mbps	...
Main features	...	<ul style="list-style-type: none"> <li>• PoE OUT 24 V - port WAN, (4, 5+; 7, 8-)</li> <li>• Wi-Fi 5</li> <li>• Easy and uniform management system for many devices</li> <li>• Intuitive installation and configuration of many advanced functions</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> </ul>
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.3	...
Operation temp	...	-10 °C ... 50 °C
Permissible relative humidity	...	5 % ... 95 %
RTSP URL	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
PC client access ports	3000, 3001	...
Mobile client access ports	3000, 3001	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Alarm inputs / outputs	16 / 4	...
Motion Detection	✓	...
Intelligent image analysis	—	...
USB	1 x USB 2.0 + 1 x USB 3.0	...
RS232	1 pcs	...
RS485	1 pcs	...
Mouse support	✓	...
IR remote controller in the set	—	...

Main features	<ul style="list-style-type: none"> <li>• Possibility of operation the disks in RAID JBOD/0/1/5/6/10 array</li> <li>Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• parking detection</li> <li>• heat map</li> <li>• scene changing</li> <li>• signal loss indication</li> <li>• License plate recognition</li> <li>• detection of persons on duty</li> <li>• detection of people gathering</li> <li>• Parking monitoring mode</li> <li>• protective helmet detection</li> <li>• people counting</li> <li>• advanced face capture features - (max 100 000 faces in the database)</li> </ul> </li> </ul>	...
Power supply	12 V DC / 5 A (power adapter included)	<ul style="list-style-type: none"> <li>• 24 V DC / 830 mA - (power adapter included)</li> <li>• PoE 24 V - Port 1</li> </ul>
Weight	3.32 kg	0.28 kg
Dimensions	440 x 355 x 76 mm	89 x 90 x 89 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Vietnamese, German, Ukrainian, Portuguese	...
Manufacturer / Brand	TIANDY	UBIQUITI
Guarantee	3 years	2 years