



	IP CAMERA IPC-HFW1439TL1-A-IL Smart Dual Light - 3.7 Mpx 2.8 mm DAHUA	LI-ION BATTERY BAT-INR18650-30Q/AKU 3.6 V SAMSUNG
		
	680.00 PLN 680.00 PLN	42.84 PLN 42.84 PLN
Rated voltage	...	3.6 V
Standard	TCP/IP	...
Battery capacity	...	3.0 Ah
Battery charging voltage	...	max. 4.2 V
Sensor	1/2.9 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Battery charging current	...	1.5 A - standard charging 4.0 A - fast charging
Maximal output current	...	15.0 A - continuous
Minimum allowable battery voltage (End voltage / Cut off)	...	2.5 V
Battery type	...	Li-Ion
Size	...	18650
Protection	...	—
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	94 °	...
Range of IR illumination	30 m	...
White light LED illuminator range	30 m	...
S/N ratio	> 56 dB	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio detection • Compliance with the AAC standard 	...
Main stream frame rate	25 fps @ 3.7 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection - max. 4 configurable zones • Privacy zones - max. 4 • Intelligent image analysis : Human detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 530 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 6.4 W @ 12 V DC • ≤ 7.7 W @ PoE 	...
Housing	Compact - Metal	...
Color	White + Black	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.31 kg	0.046 kg
Dimensions	198 x 80 x 76 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	DAHUA	SAMSUNG
Guarantee	3 years	2 years

