



	IP CAMERA IPC3614LE-ADF28K-G - 4 Mpx 2.8 mm UNIVIEW	IP CAMERA IPC-HDW2441TM-S-0280B WizSense - 4 Mpx 2.8 mm DAHUA
		
	642.51 PLN 642.51 PLN	1058.00 PLN 1058.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/3 " Progressive Scan CMOS	1/2.9 " Progressive Scan CMOS
Matrix size	4 Mpx	5 Mpx
Scanning system	Progressive	...
S/N ratio	> 52 dB	...
RS-485 interface	—	...
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	• 101 ° (manufacturer data) • 96 ° (our tests result)	95 °
Range of IR illumination	30 m	30 m
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	• Microphone built-in • Audio transmission via network • Audio detection	• Microphone built-in • Audio detection
Main stream frame rate	25 fps @ 3.7 Mpx	• 20 fps @ 4 Mpx • 25 fps @ 3.7 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP
WEB Server	Built-in	Built-in
Max. number of on-line users	32	20
ONVIF	✓	21.12
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	DHCP or 192.168.1.13	192.168.1.108
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80, 37777
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	37777

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	80	37777
Port ONVIF	80	80
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette) 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • AGC - Automatic Gain Control • Mirror - Mirror image • ICR - Movable InfraRed filter • Day/night mode • Auto White Balance • Motion Detection - max. 4 zones • Privacy zones - max. 4 • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles, video tampering
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	rtsp://admin:hasio@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasio@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Housing	Dome, Metal + Plastic	Dome - Metal + Plastic
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 350 mA
Power consumption	≤ 6 W	max. 5.1 W @ PoE max. 4.2 W @ 12 V DC
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.37 kg	0.51 kg
Dimensions	Ø 118 x 95 mm	Ø 122 x 99 mm
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	UNIVIEW	DAHUA
Guarantee	3 years	3 years