



	CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/RD	IP VANDALPROOF CAMERA DS-2CD2743G2-IZS(2.8-12MM) 4 Mpx - MOTOZOOM Hikvision
		
	3.79 PLN 3.79 PLN	1920.00 PLN 1920.00 PLN
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Inner conductor	4.0 mm ² - Stranded wire Cu - Tin-plated	...
Rated voltage	600 V / 1000 V AC 1800 V DC	...
Resolution	...	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Outer coating	Ø 5.0 mm - Non-halogen plastic	...
Lens	...	2.8 ... 12 mm - Motozoom
View angle	...	• 96 ° ... 29 ° (manufacturer data) • 97 ° ... 30 ° (our tests result)
Range of IR illumination	...	40 m
RS-485 interface	...	—
Main features	<ul style="list-style-type: none"> • UV radiation resistance • Ozone resistance • Hydrolysis resistance • Resistant to oils and aggressive chemicals • Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1) • The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion • Increased mechanical strength of the outer coating • Expected lifetime : 25 years 	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Coating color	Red	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1

Audio	...	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour, SSL / TLS, PPPoE
WEB Server	...	Built-in, Web Viewer
Max. number of on-line users	...	6
ONVIF	...	18.12
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main stream frame rate	...	25 fps @ 4 Mpx

Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Mirror - Mirror image • Day/Night mode (color/b&w/auto) • WB - White Balance • AGC - Automatic Gain Control • Configurable Privacy Zones • Motion Detection • Sharpness - sharper image outlines • Intelligent image analysis : Filtering of false alarms based on the recognition of persons and vehicles : intrusion, crossing the line (tripwire), face detection
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 880 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 12.5 W @ PoE (802.3af) • ≤ 10.5 W @ 12 V DC
Housing	...	Dome - Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	IK10
Operation temp	...	-30 °C ... 60 °C
Weight	...	1.23 kg
Dimensions	...	Ø 153 x 112 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	311313608
Guarantee	2 years	3 years