



	<a href="#">INSULATION RESISTANCE METER + RCD TESTER UT-526 UNI-T</a>	<a href="#">CABLES TESTER HDMI UT-681-HDMI UNI-T</a>
		
	890.13 PLN 890.13 PLN	92.79 PLN 92.79 PLN
Tested cables	...	HDMI, mini HDMI
Resistance measurement	<ul style="list-style-type: none"> <li>• Test voltage 250 V : 0.05 MΩ ... 200 MΩ</li> <li>• Test voltage 500 V : 0.05 MΩ ... 300 MΩ</li> <li>• Test voltage 1000 V : 0.05 MΩ ... 500 MΩ</li> </ul>	...
Measuring accuracy	0.05 MΩ ... 500 MΩ ± (5% + 5)	...
Open circuit voltage	Test voltage + 10 %	...
Test current	0.9 mA ... 1.1 mA	...
Short-circuit current	< 1.8 mA	...
AC voltage measurement	0 V ... 440 V ± (2% + 3) @ 1 V	...
DC voltage measurement	0 V ... 440 V ± (2% + 3) @ 1 V	...
Measurement of small resistances	0.01 Ω ... 2000 Ω ± (2% + 5)	...
Frequency measurement	20 Hz ... 100 Hz - for reference only	...
Test of RCDs	<ul style="list-style-type: none"> <li>• Working voltage: 220V ± 10 %</li> <li>• Test current: 10mA / 30mA / 100mA / 300mA</li> <li>• Switch-off time ranges : <ul style="list-style-type: none"> <li>- 0 ... 2000 ms ± (5% + 2) @ 10 mA</li> <li>- 0 ... 500 ms ± (5% + 2) @ 30 mA</li> <li>- 0 ... 300 ms ± (5% + 2) @ 100 mA</li> <li>- 0 ... 300 ms ± (5% + 2) @ 300 mA</li> </ul> </li> </ul>	...
Automatic change of measuring ranges	—	...
RS-232	—	...
USB	—	...

Main features	<ul style="list-style-type: none"> <li>• Warning of using high voltage during the measurement,</li> <li>• Phase switch 0° / 180° during RCD test,</li> <li>• Automatic identification of AC/DC voltage,</li> <li>• Large, readable LCD display with backlight,</li> <li>• Buzzer,</li> <li>• Low battery level alarm,</li> <li>• Aesthetic and solid construction</li> </ul>	<ul style="list-style-type: none"> <li>• Test for the presence of a short circuit, open circuit</li> <li>• Single / full scan mode</li> <li>• Automatic shutdown after 10 minutes of inactivity</li> <li>• Low battery level alarm</li> </ul>
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	≤ 85 % (non-condensing)	...
Power supply	6 x 1.5V, type AA/LR6/FR6 battery - included	9V, type 6F22 battery (included)
Weight	0.45 kg	0.132 kg
Dimensions	150 x 100 x 71 mm	103 x 96 x 29 mm
Manufacturer / Brand	UNI-T	UNI-T
Guarantee	2 years	2 years