





	BATTERY 12.8V/100AH/LIFEPO4-GC Green Cell	PARKING SENSOR LED LIGHTING CONTROLLER PARKING-SENSOR/BLEBOX 7... 24 V DC	RJ-45 PLUG INTERNAL SHIELD RJ45/WP-Y/IN	RJ-45 PLUG SHIELD RJ45/WP-C*P10
				
	1935.16 PLN 1935.16 PLN	121.15 PLN 121.15 PLN	0.15 PLN 0.15 PLN	1.76 PLN 1.76 PLN
Battery capacity	100 Ah
Battery charging current	50 A
Battery type	LiFePO ₄ lithium-iron-phosphate battery
In package	10 pcs The price for package
Application	...	<ul style="list-style-type: none"> • It shows the distance between the moving object and the sensor by using LED lighting • Works with LED lighting - (RGB) 7-24V LED strips
Application	RJ-45 modular plug internal shield	RJ-45 modular plug shield
Material	Plastic	Rubber
Rated voltage	12.8 V	7 ... 24 V DC
Maximal total load	...	56 ... 192 W
Battery lifetime	> 10 years (> 2000 cycles @ 85 % DoD)
Total maximal current	...	8 A
Connector	M8 screw
Number of inputs	...	0
Number of outputs	...	4
Connector type	...	screw terminals
Wireless	...	—
Mobile phones support	...	—

Main features	...	<ul style="list-style-type: none"> • Ultrasonic sensor, • Outputs : "Open Collector" (OC) type 250 mA, • Distance range of the virtual wall from the sensor : 2 ... 250 cm, • Operation modes (distances to virtual wall) : <ul style="list-style-type: none"> - Green : 140 cm (safe distance) - Blue : 48 ± 4 cm (obstacle close) - Red : 17 ± 3 cm (stop the vehicle) - Red (blinking) : 4 ± 2 cm (stop the vehicle immediately) • Additional output for space occupancy signaling, • Small dimensions
Housing	...	Self-extinguishing
"Index of Protection"	...	IP20
Color	...	Black	Yellow	Black
Operation temp	...	-20 °C ... 50 °C
Weight	10.6 kg	0.06 kg	0.0005 kg	...
Dimensions	329 x 172 x 217 mm	51 x 58 x 25 mm	20.3 x 11.7 x 7.9 mm	...
Manufacturer / Brand	Green Cell	BleBox
Guarantee	2 years	2 years	2 years	2 years

