



	<a href="#">IP CAMERA TC-C38WQ SPEC:15W/E/Y/2.8MM/V4.2 - 8 Mpx 2.8 mm TIANDY</a>	<a href="#">HEX HEAD SCREW SS-M8X20/KL-8.8</a>
		
	1237.00 PLN 1237.00 PLN	0.58 PLN 0.58 PLN
Size	...	M8
Standard	IP	...
Material	...	Steel galvanized
Strength class	...	8.8
Main features	...	DIN 933 compliance
Wrench size	...	13 mm
Thread length	...	20 mm
Resolution	3840 x 2160 - 8 Mpx , 3072 x 2048 - 6 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	105 °	...
Range of IR illumination	50 m	...
White light LED illuminator range	15 m	...
Memory card slot	Micro SD card support up to 512GB	...
Image compression method	S+265 / H.265 / H.264	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio input</li> <li>• Audio output</li> <li>• Speaker built-in</li> <li>• Bi-directional audio streaming support</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul>	...
Main stream frame rate	20 fps @ 8 Mpx 25 fps @ 3.7 Mpx	...
Interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	2	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

ONVIF	✓	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Default IP address	192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> <li>• video tampering</li> <li>• Audio detection</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• Early Warning (EW) - combination of white light warning with audio signals</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Motion Detection</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 590 mA</li> </ul>	...
Power consumption	≤ 8.5 W	...
Housing	Compact - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-40 °C ... 65 °C	...
Weight	0.52 kg	0.012 kg
Dimensions	170 x 71 x 71 mm	...
Supported languages	Polish, English, Albanian, French, Hebrew, Spanish, Dutch, Korean, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	...
Guarantee	3 years	2 years