



	POE SWITCH, EXTENDER XPOE-4-11A-HS 4-PORT ATTE	ROUTER RG-EG310GH-E REYEE
		
	185.00 PLN 185.00 PLN	1298.00 PLN 1298.00 PLN
Standards	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z
LAN ports	<ul style="list-style-type: none"> • 1 x LAN + PoE IN - Port LAN 1, • 3 x LAN + PoE OUT - LAN2 ... LAN4 ports 	<ul style="list-style-type: none"> • 6 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)
Management	—	...
WAN interface	...	<ul style="list-style-type: none"> • 1 x WAN x 10/100/1000 Mbps (RJ-45)
LED diodes	Power, LAN	...
LED indicators	...	Status, Link/Act
Transmission speed	10 / 100 Mbps	...
DDNS	...	✓
DHCP server	...	✓
Port USB	...	—
Firmware update	...	✓
Power supply PoE	...	—
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN2 ... LAN4 ports • 13 W / 25 W @ PoE (802.3af/at) - LAN2 ... LAN4 ports 	...
Protections	...	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks
Management interface	...	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser

Mobile phones support	...	Android: Free application Ruijie Rejee iOS (iPhone): Free application Ruijie Rejee
Main features	<ul style="list-style-type: none"> • Possibility to power up to 3 PoE 802.3at/af or PASSIVE receivers • Possibility to connecting in cascade • The ability to turn off the power on selected PoE ports • The output PoE voltage is equal to the input voltage • Overvoltage protection • Short-circuit protection - LAN 1 	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button
Power supply	<ul style="list-style-type: none"> • 44 ... 56 V DC - LAN 1, • 12 ... 56 V DC - LAN 2 ... LAN 4 	100 ... 240 V AC, 50 / 60 Hz
Power consumption	...	≤ 15 W
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.04 kg	2.4 kg
Dimensions	94 x 41 x 18 mm	440 x 207 x 44 mm
Manufacturer / Brand	ATTE	RUIJIE / REYEE
Guarantee	3 years	2 years