



|                                 |  |  |
|---------------------------------|--|--|
|                                 | <a href="#">ROUTER WIFI RG-EG105GW-X Wi-Fi 6, 574 Mbps + 2404 Mbps REYEE</a>       | <a href="#">AHD, HD-CVI, HD-TVI, CVBS CAMERA DS-2CE79H0T-IT3ZF(2.7-13.5mm)(C) - 5 Mpx Hikvision</a>  |
|                                 |   |    |
|                                 | 976.00 PLN<br>976.00 PLN   | 525.00 PLN<br>525.00 PLN   |
| Frequency range                 | 2.4 GHz, 5 GHz   | ...  |
| Standard                        | ...  | AHD, HD-CVI, HD-TVI, CVBS  |
| Sensor                          | ...  | Progressive Scan CMOS  |
| Matrix size                     | ...  | 5 Mpx  |
| Antenna type                    | 2x2 MIMO - built-in<br>• 5 dBi @ 2.4 GHz<br>• 5 dBi @ 5 GHz                        | ...  |
| Standards                       | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac/ax, Wi-Fi 6   | ...  |
| Baud rates                      | 574 Mbps @ 2.4 GHz + 2404 Mbps @ 5 GHz   | ...  |
| LAN ports                       | • 1 x LAN<br>10/100/1000 Mbps (RJ-45)<br>• 3 x LAN/WAN<br>10/100/1000 Mbps (RJ-45) | ...  |
| WAN interface                   | 1 x WAN x<br>10/100/1000 Mbps (RJ-45)  | ...  |
| Resolution                      | ...  | 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps ,<br>2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps ,<br>1920 x 1080 - 1080p @ HD-TVI,<br>25 fps<br>960 x 576 - 960H @ CVBS |
| Range of IR illumination        | ...  | 40 m   |
| LED indicators                  | Status, Link/Act, Mesh   | ...  |
| IR illuminator power adjustment | ...  | Automatic  |
| DDNS                            | ✓  | ...  |
| DHCP server                     | ✓  | ...  |
| Port USB                        | ✓  | ...  |
| Lens                            | ...  | 2.7 ... 13.5 mm - Motozoom   |
| Firmware update                 | ✓  | ...  |
| Power supply PoE                | —  | ...  |
| View angle                      | ...  | • 95 ° ... 26 ° (manufacturer data)<br>• 93 ... 25 (our tests result)  |

|                       |   |  |
|-----------------------|---|--|
| Protections           | <ul style="list-style-type: none"> <li>• TCP scan blocking</li> <li>• ACL</li> <li>• IP-MAC Binding</li> <li>• MAC addresses filtering</li> <li>• Support for dynamic ARP mapping and static table</li> <li>• NAT / NAPT</li> <li>• Port Mapping</li> <li>• Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks</li> </ul> | ...  |
| Video output          | ...   | 1 x AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω, BNC socket  |
| Management interface  | <ul style="list-style-type: none"> <li>• Ruijie Cloud Central Management System</li> <li>• Configuration using the Ruijie Reeye application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>  | ...  |
| Mobile phones support | Android: Free application <a href="#">Ruijie Reeye</a><br>iOS (iPhone): Free application <a href="#">Ruijie Reeye</a>   | ...  |
| Main features         | ...   | <ul style="list-style-type: none"> <li>• Motozoom lens</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• BLC - Back Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul> |
| OSD menu              | ...   | ✓  |
| Housing               | ...   | Dome, Metal  |
| Color                 | ...   | White  |
| "Index of Protection" | ...   | IP67   |

|                               |  |                    |
|-------------------------------|--|--------------------|
| Main features                 | <ul style="list-style-type: none"> <li>• Support for Reye Mesh technology</li> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• Reboot schedule</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul> | ...                |
| Operation temp                | ...  | -40 °C ... 60 °C   |
| Power supply                  | 100 ... 240 V AC, 50 / 60 Hz   | 12 V DC / 520 mA   |
| Power consumption             | ≤ 20 W   | ≤ 6.2 W            |
| Supported languages           | ...  | English            |
| Operation temp                | 0 °C ... 40 °C   | ...                |
| SAP Code                      | ...  | 300615088          |
| Permissible relative humidity | 10 % ... 90 % (non-condensing)   | ...                |
| Weight                        | 1.1 kg   | 0.6 kg             |
| Dimensions                    | 315 x 188 x 188 mm   | 134 x 124 x 110 mm |
| Manufacturer / Brand          | RUIJIE / REYEE   | Hikvision          |
| Guarantee                     | 2 years  | 3 years            |