



	ACCESS CONTROLLER MODULE MC16-PAC-EX-6 ROGER	NVR DS-7732NXI-I4/S(E) 32 CHANNELS ACUSENSE Hikvision
		
	5050.00 PLN 5050.00 PLN	5299.00 PLN 5299.00 PLN
Standard	...	TCP/IP
Number of served transitions	6	...
Supported resolutions	...	max. 32 Mpx
Inputs	36	...
Outputs	24	...
Number of users	max. 12000 - Number of identifiers	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Video outputs	...	2 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS There is a possibility to configure a SPOT function on one of the output
Number of permissions per ID	100	...
Buffer memory	8 000 000 events buffer	...
MCT readers support	16 pcs	...
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	...	1 pcs CINCH
Readers connections	4 pcs - Wiegand / PRT	...
Number of login points	12	...
Audio outputs	...	1 pcs CINCH
Number of access terminals	24	...
Number of access zones	12	...
Number of alarm zones	12	...
Number of automation nodes	12	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Bitrate	...	max. 256 Mbps
Battery backup support	12 V / 7 Ah	...
Supported hard drives	...	4 x 10 TB SATA + 1 x eSATA

Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 16 channels in the same time @ 1080p
Network interface	...	2 x RJ-45 10/100/1000 Base-TX
Main features	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	...
Network functions	...	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Network protocols	...	TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS
ONVIF	...	✓
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) Android: Free application Hik-Connect iOS: Free application Hik-Connect
Web browser access ports	...	80, 8000



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	...	8000
Mobile client access ports	...	8000
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
USB	...	2 pcs USB 2.0 1 pcs USB 3.0
Serial ports	...	2 pcs RS-485 1 pcs RS-232
Alarm inputs / outputs	...	16 / 9
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others
Motion Detection	...	2.0
Intelligent image analysis	...	✓
Main features	...	<ul style="list-style-type: none"> • NVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Face recognition, Motion detection with human/vehicle silhouette recognition • Filtering of false alarms based on the recognition of persons and vehicles • Comparison of faces with images from the database • supports 4 types of facial attributes extraction • Support for up to 16 face databases, including 50 000 face images • Smart search for a person based on a face photo • Cooperation with POS (Point of Sale) terminals • Power outputs : 12 V DC / 1 A, 12 V DC / 0.5 A (controlling) <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • people counting
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	100 ... 240 V AC / 50 ... 60 Hz
Power consumption	...	max. 30 W (without HDD)
Operation temp	5 °C ... 40 °C	-10 °C ... 55 °C
Weight	0.14 kg	4.1 kg
Dimensions	175 x 72 x 30 mm	445 x 402 x 75 mm, RACK 19", 1.5U

Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	ROGER	Hikvision
SAP Code	...	303618605
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00