



	SWITCH POE IP-9-11-L2 8-PORT ATTE	SWITCH POE IP-8-20-H 8-PORT ATTE
		
	753.11 PLN 753.11 PLN	1259.00 PLN 1259.00 PLN
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-TX - Uplink • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE
Management	—	—
LED diodes	Power, LAN	Power, LAN
Transmission speed	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports • 10 / 100 / 1000 Mbps : 2 Port LAN
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports
Maximal total power	96 W	96 W
Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 	...

Main features	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement 	<ul style="list-style-type: none"> • Pin numbers for RJ-45 connector : 1/2, 3/6 - Wires to data transmission ; 4/5, 7/8 - Power supply • Possibility to connecting in cascade • Efficiency : 92 % @ 90 W • Built-in switching power supply : 48 V DC / 96 W • PSU thermal protection • Short-circuit protection • Overload protection • TAMPER switch indicating open the cover • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • Electronic fuse independently for each PoE channel • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • Main cable entries on the back of the enclosure • "Index of Protection" : IP20
Power supply	230 V AC - cable terminals	180 ... 240 V AC - Built-in switching power supply
Weight	1.05 kg	4.33 kg
Dimensions	248 x 222 x 96 mm	400 x 450 x 140 mm
Manufacturer / Brand	ATTE	ATTE
Guarantee	3 years	3 years