



	SWITCH POE GTX-CLM1-10-8G2G 8-PORT	CIRCUIT BREAKER HN-B32/3 THREE-PHASE 32 A B TYPE EATON
		
	600.00 PLN 600.00 PLN	76.88 PLN 76.88 PLN
Device type	...	Circuit Breaker, Three-phase
Rated current	...	32 A
Number of poles	...	3
Tripping curves	...	B type
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (2 x Hi-PoE + 6 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
Breaking capacity	...	6000 A
Management	✓	...
Rated voltage	...	<ul style="list-style-type: none"> • 230 V AC / 50 Hz • 400 V AC / 50 Hz
Connectors type	...	screw terminals
Transmission speed	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	...
Wire gauge	...	1 mm ² - 25 mm ²
Width in 17.5 mm modules	...	3
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Default IP address	192.168.2.1	...
Default admin user / password	admin / admin	...
Manufacturer / Brand	...	EATON
Maximal output power	<ul style="list-style-type: none"> • 90 W / port Hi-PoE - 1, 2 ports • 30 W / port PoE - 3 ... 8 ports 	...
Maximal total power	120 W	...

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto-learning and Auto-aging functions support for MAC addresses • QoS - mechanisms, which provide the high quality of transmission • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Contact position indicator • Possibility of sealing
LED diodes	PWR, PoE, Link/Act	...
Certificates	CE, FCC, RoHS	...
Protections	Overvoltage \pm 4 kV	...
Power supply	48 ... 57 V DC, Power adapter included	...
Housing	Metal	Plastic, DIN, TS-35 rail mounting
Operation temp	-10 °C ... 55 °C	...
Weight	0.45 kg	0.322 kg
Dimensions	185 x 95 x 27 mm	52.5 x 84.5 x 73 mm
Guarantee	2 years	2 years