



	<a href="#">SMART THERMOSTATIC HEAD ATLO-TH2-TUYA Zigbee, Tuya Smart</a>	<a href="#">ACCESS CONTROLLER MC16-PAC-ST-3-KIT ROGER</a>
		
	130.83 PLN 130.83 PLN	2725.00 PLN 2725.00 PLN
Application	radiator valve control head	...
Number of served transitions	...	3 (two-way)
Number of supported readers	...	12
Number of users	...	unlimited (purchase of the appropriate license required)
Measurement range	0 °C ... 60 °C	...
Measuring accuracy	± 1 °C	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Buffer memory	...	8 000 000 events buffer
Manual temperature control	5 °C ... 35 °C	...
Number of access zones	...	6
Number of alarm zones	...	6
Battery backup support	...	12 V / 20 Ah
Communication	...	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>
Power supply	2 x battery 1.5 V LR6 (AA)	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• Possibility of manual change of the valve position,</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Temperature Sensor : NTC thermistor</li> <li>• LED display</li> <li>• LED indication</li> <li>• Heating suppression if a window is open</li> <li>• Anti-scale function</li> <li>• Child Lock - securing the device against children</li> <li>• Time mode</li> <li>• Anti-freezing function</li> <li>• Failure signaling</li> <li>• Low battery level alarm</li> </ul>	<ul style="list-style-type: none"> <li>• Metal housing</li> <li>• The MCX4D I/O expander included</li> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul>
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Housing	Plastic	...
Color	White	...
Operation temp	0 °C ... 50 °C	5 °C ... 40 °C
Weight	0.146 kg	4.08 kg
Manufacturer / Brand	...	ROGER
Dimensions	Ø 55 x 95 mm	405 x 365 x 120 mm
Guarantee	2 years	3 years