




	OMNIDIRECTIONAL ANTENNA MAGNET	IP CAMERA APTI-20PV2-36WP-ECO - 3.7 Mpx 3.6 mm
		
	105.30 PLN 105.30 PLN	120.00 PLN 120.00 PLN
Standard	...	IP
Receiving channels	• 6 ... 12, • 21 ... 49	...
Gain	30 ... 33 dB, 44 dB (max)	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	...	1/3 " Progressive Scan CMOS
Lens	...	3.6 mm
Frequency range	174 ... 230 MHz, 470 ... 698 MHz	...
View angle	...	73 ° (manufacturer data)
Polarization	Horizontal	...
Range of IR illumination	...	25 m
Impedance	75 Ω	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Main stream frame rate	...	25 fps @ 3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in - port 80
Max. number of on-line users	...	10
ONVIF	...	19.12
Intelligent image analysis	...	• intrusion • motion detection based on human detection
Main features	<ul style="list-style-type: none"> • Reception angle : 360 ° • Length of the cable : 3.5 m and 1.5 m • Diode voltage indicator • High resistance to wind and weather • Very easy installation • Antenna cable + F plug, Antenna separator + IEC plug, Car lighter plug, Connecting cable TV - IEC, magnetic base - included 	...

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Power supply	12 V / 24 V DC, 30 mA Car lighter plug	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 310 mA
Power consumption	...	≤ 3.7 W
Housing	...	Dome - Plastic
Color	...	White
"Index of Protection"	...	—
Mechanical protection class	...	—
Operation temp	...	-20 °C ... 60 °C
Weight	0.23 kg	0.2 kg

Dimensions	Ø 280 x 80 mm	Ø 110 x 88 mm
Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Ukrainian, Hungarian, Italian
Manufacturer / Brand	WIEDYSKA	APTI
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00