





	<a href="#">IP CAMERA DS-2CD2087G2-LU(4MM) ColorVu - 8.3 Mpx Hikvision</a>	<a href="#">LED LIGHTING CONTROLLER FUT035S 2.4 GHz, CCT 12... 24 V DC MiBOXER / Mi-Light</a>	<a href="#">PLUG F/5.9-CFS</a>	<a href="#">PLUG F/6.5*P100</a>
				
	2435.00 PLN 2435.00 PLN	19.60 PLN 19.60 PLN	0.48 PLN 0.48 PLN	60.00 PLN 60.00 PLN
Standard	IP	...	...	...
Application	...	Works with LED lighting - white LED strips with adjustable color temperature (CCT) 12-24V	...	...
In package	...	...	...	<b>100 pcs The price for package</b>
Rated voltage	...	12 ... 24 V DC	...	...
Connector type	...	...	"F" Straight plug	"F" Straight plug
Attachment of connector elements	...	...	Twisted-on	Twisted-on
Shield fastening	...	...	Twisting-on	Twisting-on
Wire mounting	...	...	—	—
Maximal total load	...	• 144 W @ 12 V, • 288 W @ 24 V	...	...
Application	...	...	Coaxial cable	Coaxial cable
Total maximal current	...	12 A	...	...
Number of inputs	...	1	...	...
Cable diameter	...	...	max. 5.9 mm	max. 6.5 ± 0.05 mm
Number of outputs	...	2 (power)	...	...
Impedance	...	...	75 Ω	75 Ω
Material	...	...	Metal	Metal
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 5.8 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...	...
Sensor	1/1.2 " Progressive Scan CMOS	...	...	...
Connector type	...	• screw terminals, • 5.5/2.1 socket / screw terminals - power input	...	...
Lens	4 mm	...	...	...
Wireless	...	2.4 GHz	...	...
View angle	88 °	...	...	...
Radio communication range (at open area)	...	30 m	...	...
White light LED illuminator range	40 m	...	...	...
Memory card slot	Micro SD card support up to 256GB	...	...	...
Main features	...	The repeater function allows you to transfer control to subsequent FUT035S / FUT036S / FUT038S / FUT039 modules even beyond the direct range of the remote control	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...
Alarm inputs / outputs	—	...	...	...
Operation temp	...	-10 °C ... 40 °C	...	...
Audio	• Microphone built-in • Audio transmission via network • Noise suppression and echo cancellation • Compliance with the AAC standard	...	...	...
Main stream frame rate	• 20 fps @ 8.3 Mpx • 25 fps @ 4 Mpx	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network interface	10/100 Base-T (RJ-45)	...	...	...
WEB Server	Built-in	...	...	...
Max. number of on-line users	6	...	...	...
ONVIF	✓	...	...	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• face detection</li> <li>• detection of entry into the area / exit from the area</li> <li>• scene changing</li> <li>• intrusion</li> </ul>	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> </ul>	...	...	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	Access by a cloud (P2P) • The <a href="#">Tuya Smart</a> free application on Android • The <a href="#">Tuya Smart</a> free application on iOS	...	...
Default IP address	192.168.1.64	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...
Web browser access ports	80	...	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P)	...	...	...
Mobile client access ports	8000	...	...	...
Port ONVIF	80	...	...	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 580 mA</li> </ul>	...	...	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 8.5 W @ PoE</li> <li>• ≤ 7 W @ 12 V DC</li> </ul>	...	...	...
Housing	Compact, Metal	Plastic	...	...
Color	White	White	...	...
"Index of Protection"	IP67	...	...	...
Mechanical protection class	—	...	...	...
Operation temp	-30 °C ... 60 °C	...	...	...
Weight	0.84 kg	0.03 kg	0.002 kg	0.005 kg
Dimensions	215 x 79 x 79 mm	75 x 36 x 17 mm	Ø 11 mm x 18 mm	Ø 11 mm x 20 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	Hikvision	MiBOXER / Mi-Light	...	...
SAP Code	311314549	...	...	...
Guarantee	3 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00