



	<a href="#">IP CAMERA DS-2CD1047G2H-LIU(2.8MM) ColorVu - 3.7 Mpx</a> <a href="#">Hikvision</a>	<a href="#">DIRECTIONAL ANTENNA</a> <a href="#">1/5-12/DAB DIPOL</a>
		
	815.00 PLN 815.00 PLN	33.66 PLN 33.66 PLN
Standard	IP	...
Frequency range	...	170 ... 230 MHz
Gain	...	2 dBi
Polarization	...	Horizontal / Vertical
Impedance	...	75 Ω
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Main features	...	<ul style="list-style-type: none"> <li>• Number of elements : 1</li> <li>• Matching transformer included</li> </ul>
Sensor	1/3 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	115 °	...
White light LED illuminator range	30 m	...
Range of IR illumination	30 m	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul>	...
Main stream frame rate	20 fps @ 3.7 Mpx	...
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	—	...

Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• SVC (Scalable Video Coding) - technology enabling the transfer ... of several sub-streams of different quality within one stream</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> </ul>	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 7.5 W @ PoE</li> <li>• ≤ 6 W @ 12 V DC</li> </ul>	...
Housing	Compact, Metal + Plastic	...
Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.3 kg	...
Dimensions	Ø 70 x 173 mm	700 x 200 x 100 mm
Supported languages	English, Ukrainian	...

Manufacturer / Brand	Hikvision	DIPOL
SAP Code	311325490	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00