




	<a href="#">ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/400 SPRAY 400 ml AG TERMOPASTY</a>	<a href="#">ACCESS CONTROLLER DS- K2602T Hikvision</a>	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-ST-2 ROGER</a>
			
	21.44 PLN 21.44 PLN	2460.00 PLN 2460.00 PLN	1390.00 PLN 1390.00 PLN
Number of served transitions	...	...	2 (two-way)
Package	Spray 400 ml	...	...
Application	Ideal for removing dirt from optical components	...	...
Number of users	...	...	unlimited (purchase of the appropriate license required)
Number of supported readers	...	<ul style="list-style-type: none"> <li>• 4 pcs @ RS-485,</li> <li>• 4 pcs @ Wiegand</li> </ul>	8
Number of media per ID	...	...	8 - Proximity card, PIN code, fingerprint, etc.
Buffer memory	...	...	8 000 000 events buffer
Number of access zones	...	...	4
Number of alarm zones	...	...	4
Battery backup support	...	max. 7 Ah	12 V / 7 Ah
Input lines	...	<ul style="list-style-type: none"> <li>• 4 pcs - Alarm inputs,</li> <li>• 2 pcs - Reed switch ,</li> <li>• 2 pcs - Door/gate opening button,</li> <li>• 5 pcs - Tamper</li> </ul>	...
Output lines	...	<ul style="list-style-type: none"> <li>• 2 pcs - Lock relay,</li> <li>• 4 pcs - Relay</li> </ul>	...
Communication	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand (w26 / w34),</li> <li>• Open Supervised Device Protocol (OSDP)</li> </ul>	<ul style="list-style-type: none"> <li>• Ethernet - RJ-45 socket</li> <li>• RACS 5 v2 (Roger)</li> <li>• RS-485 interface</li> </ul>
Power supply	...	100 ... 240 V AC	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 300000 events</li> <li>• Remote programming from PC</li> <li>• Metal housing</li> </ul>	<ul style="list-style-type: none"> <li>• Integrated support in VISO ST software</li> <li>• Functions in the VISO ST system: <ul style="list-style-type: none"> <li>- MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system : 128</li> </ul> </li> </ul>
Operation temp	...	-20 °C ... 65 °C	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)	10 % ... 95 % (non-condensing)
Weight	0.36 kg	4.6 kg	0.14 kg
Dimensions	Ø 66 x 187 mm	373 x 345 x 98 mm	175 x 72 x 30 mm
Manufacturer / Brand	AG TERMOPASTY	Hikvision	ROGER
SAP Code	...	302913795	...
Guarantee	...	3 years	3 years