

	<u>IP SPEED DOME CAMERA OUTDOOR OMEGA-51P18-8P - 5 Mpx 5.35 ... 96.3 mm</u>	<u>DIGITAL UNIPHONE MP800/3.5 ACO</u>
		
	1051.20 PLN 1051.20 PLN	595.41 PLN 595.41 PLN
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Compatibility	...	ACO CDNP, Inspiro, Familio P/PV
Matrix size	5 Mpx	...
Installation type	...	PV digital system, UTP cat. 5e, 6
LCD display	...	3.5 "
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	5.35 ... 96.3 mm	...
View angle	• 59 ° ... 3.6 ° (manufacturer data) • 48 ° ... 3.7 ° (our tests result)	...
Optical zoom	x 18	...
Auto IR illuminator	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions	...
Range of IR illumination	80 m	...
Video output	—	...
Main features	...	• Microphone built-in, • Image preview without active connection, • 7-level volume adjustment, • Relay output : 1 pcs, • Number of ring-tones : 4, • DIP SWITCH for configuration and addressing, • Connector for an additional bell button, • Full call privacy (no possibility of eavesdropping on the call), • Illuminated buttons

Rotation speed (manual control)	1 °/s ... 80 °/s (horizontal) 1 °/s ... 40 °/s (vertical)	...
Horizontal rotation range	360 ° continuous	...
Vertical rotation range	0 ° ... 93 °	...
RS-485 interface	—	...
Number of presets	255	...
Horizontal scan	✓	...
Image compression method	H.265 / H.264	...
Protections	Overvoltage	...
Alarm inputs / outputs	—	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	...
Main stream frame rate	• 20 fps @ 5 Mpx • 25 fps @ 4 Mpx	...
WEB Server	Built-in	...
ONVIF	✓	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin The administrator password should be set at the first start	...
Web browser access ports	80	...
Port ONVIF	8999	...
RTSP URL	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream	...
Route settings	8	...
OSD menu	preset 95	...

Main features	• Intelligent image analysis : intrusion, motion detection based on human detection, video tampering • ROI - improve the quality of selected parts of image • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • Auto White Balance • IR illuminator optimization • Mirror - Mirror image • Privacy zones - max. 4	...
Power supply	• PoE (802.3at), • 12 V DC / 3 A (power adapter included)	15 V DC, 280 mA (power adapter not included)
Power consumption	≤ 33 W	...
Housing	Speed Dome, Metal	Plastic
Color	White + Black	White
"Index of Protection"	IP66	...
Operation temp	-20 °C ... 60 °C	10 °C ... 40 °C
Weight	1.5 kg (with bracket)	0.250 kg
Dimensions	200 x 269 x 137 mm (with bracket)	198 x 82 x 27 mm
Supported languages	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	OMEGA	ACO
Guarantee	2 years	2 years