




	WORK GLOVES WG-422/M Bee-Smart WONDER GRIP	IP CAMERA DS-2CD1047G0-L(2.8MM)(C) ColorVu - 4 Mpx Hikvision	POWER DISTRIBUTION UNIT LE-049494 (6 OUTLETS) 3 m LEGRAND
			
	2255.77 HUF 2255.77 HUF	66634.62 HUF 66634.62 HUF	9042.31 HUF 9042.31 HUF
Standard	...	TCP/IP	...
Sensor	...	1/2.7 " Progressive Scan CMOS	...
Rated voltage	230 V AC / 50 Hz
Matrix size	...	4 Mpx	...
Total maximal current	16 A
Maximal total load	3680 W
Number of outlets	6 grounded outlets 16A/250V CEE 7/5
Application	<ul style="list-style-type: none"> • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly
Fuse	—
Switch	—
Wire gauge	3 x 1.5 mm ²
Resolution	...	2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Length of the cable	3 m
Lens	...	2.8 mm	...
Material	Polyester + latex coating (palm coated)
View angle	...	<ul style="list-style-type: none"> • 102 ° (manufacturer data) • 93 ° (our tests result) 	...
White light LED illuminator range	...	30 m	...
Memory card slot	...	—	...
Main features	<ul style="list-style-type: none"> • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	...	—	...
Audio	...	—	...
Supported norms	<ul style="list-style-type: none"> • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX
Size	8 / M
Main stream frame rate	...	20 fps @ 4 Mpx 25 fps @ 1080p	...
Network interface	...	10/100 Base-T (RJ-45)	...

Network protocols	...	TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTPC, NTP, UPnP, SMTP, IGMP, QoS, IPv6, UDP, Bonjour, SSL / TLS	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	6	...
ONVIF	...	18.12	...
Main features	...	<ul style="list-style-type: none"> • Possibility to turn off the LED illuminator • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Motion Detection • Mirror - Mirror image • Configurable Privacy Zones • Sharpness - sharper image outlines 	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	...	192.168.1.64	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	...	8000	...
Port ONVIF	...	80	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 380 mA 	...
Power consumption	...	≤ 4.5 W	...
Housing	...	Compact, Metal	Plastic
Color	Black + Blue	White	White / Gray
"Index of Protection"	...	IP67	...
Vandal-proof	...	—	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	...	0.42 kg	0.61 kg
Dimensions	...	166 x 77 x 77 mm	295 x 54 x 37 mm
Supported languages	...	English, Ukrainian	...
Manufacturer / Brand	WONDER GRIP	Hikvision	LEGRAND
SAP Code	...	311316776	...
Guarantee	...	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00