



	<a href="#">POLE MOUNT BD-LP09</a>	<a href="#">IP CAMERA BCS-L-TIP58FCR3L3-A11-G(2) NightColor - 8.3 Mpx 4K UHD 2.8 mm BCS Line</a>	<a href="#">CABLE TIE OPC-300X4.8/B*P100</a>
			
	124.34 DKK 124.34 DKK	3370.68 DKK 3370.68 DKK	23.42 DKK 23.42 DKK
Standard	...	TCP/IP	...
Suitable for cameras	OMEGA-21P22-6	...	...
Sensor	...	1/2.8 " Progressive Scan CMOS	...
Matrix size	...	8.3 Mpx	...
In package	...	...	<b>100 pcs The price for package</b>
Pole diameters range	Ø 90 ... Ø 120 mm	...	...
Length	...	...	300 mm
Width	...	...	4.8 mm
Material	Steel - powder painted	...	Nylon 66
Tensile strength	...	...	220 N
Resistant to	...	...	<ul style="list-style-type: none"> <li>• UV radiation</li> <li>• oil</li> <li>• gasoline</li> <li>• sea water</li> <li>• solvents</li> <li>• mold</li> <li>• diluted weak organic acids and alkaline compounds</li> </ul>
Operation temp	...	...	-10 °C ... 80 °C
Melting temperature	...	...	250 °C
Bundle diameter	...	...	3 ... 75 mm
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	...	2.8 mm F1.0	...
View angle	...	<ul style="list-style-type: none"> <li>• 106 ° (manufacturer data)</li> <li>• 100 ° (our tests result)</li> </ul>	...
Range of IR illumination	...	≤ 30 m	...
White light LED illuminator range	...	≤ 30 m	...
Min. illumination	...	0.004 Lux / F1.0, 30IRE (color)	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / H.264H / H.264B / MJPEG	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	...
RS-485 interface	...	—	...
Alarm inputs / outputs	...	1 / 1	...
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in - 2 pcs,</li> <li>• Speaker built-in,</li> <li>• Audio input,</li> <li>• Audio output,</li> <li>• Bi-directional audio streaming support,</li> <li>• Audio detection</li> </ul>	...
Main stream frame rate	...	25 fps @ 8.3 Mpx	...
Network interface	...	10/100 Base-T (RJ-45)	...
WEB Server	...	Built-in	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	...	20	...
ONVIF	...	✓	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">BCS Manager</a> • iOS (iPhone): Free application <a href="#">BCS Manager</a>	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	...	<ul style="list-style-type: none"> <li>• Active deterrence function, Alternately flashing LEDs: red and blue - frequency configuration, Alarm siren</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles</li> <li>• SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• Full Color - colorful night mode</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Light and sound alarm</li> <li>• White light (LED) illuminator built-in : 2 LEDs</li> <li>• IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, video tampering, Audio detection</li> </ul>	...
Housing	...	Compact - Metal	...
Color	White	Dark graphite	Black
"Index of Protection"	...	IP67	...
Vandal-proof	...	—	...
Power supply	...	• PoE (802.3af), • 12 V DC / 630 mA	...
Power consumption	...	• ≤ 9.1 W @ PoE • ≤ 7.6 W @ 12 V	...
Operation temp	...	-40 °C ... 60 °C	...
Weight	0.92 kg	1 kg	...
Dimensions	131 x 170 mm	289 x 95 x 85 mm	...
Supported languages	...	Polish, English	...
Manufacturer / Brand	...	BCS Line	...
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00