



	REMOTE CONTROL SREMOTE/BLEBOX Wi-Fi	INDUSTRIAL POE SWITCH S4101-16ET2GF-240-C 16-PORT SFP DAHUA
		
	113.79 PLN 113.79 PLN	2104.00 PLN 2104.00 PLN
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
LAN ports	...	<ul style="list-style-type: none"> • 16 x RJ45 10/100 Base-T (2 x Hi-PoE (802.3bt) + 14 x PoE (802.3af/at)), • 2 x port Combo: SFP (1000 Base-X) / RJ45 (10/100/1000 Base-T) - Uplink
Management	...	✓
Operation range	≤ 100 m (in open area) ≤ 40 m (internal)	...
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	...
LED diodes	...	Link, PoE, Power, System, 50 % Power, 80 % Power, 100 % Power
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 16 LAN & PoE ports, • 10 / 100 / 1000 : 2 RJ45 (Uplink) ports, • 1000 : 2 SFP (Uplink) ports
Maximal output power	...	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports • 30 W / port PoE 802.3af/at - 3 ... 16 ports
Color	White	...
Maximal total power	...	240 W
MAC addresses table	...	16k
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6

Main features	<ul style="list-style-type: none"> • Number of buttons : 4, • Number of supported devices : max. 7, • Configurable Buttons • Ability to assign a device to a button • Controlling BleBox devices • LED indication • Order confirmation • Bidirectional communication • Transmission encryption • µWiFi technology support • Control possible without Wi-Fi network available • Integrated magnets to attach to metal surfaces 	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Compliance with the LLDP protocol • View topology and network status • RESET button • Can be mounted in a Rack 19" cabinet
Certificates	...	CE, FCC
Protections	...	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	Plastic (ABS)	Metal
Power supply	<ul style="list-style-type: none"> • 2 x alkaline battery 1.5 V LR3 (AAA) (included) • Backup time ≤ 15 months 	100 ... 240 V AC @ 50 / 60 Hz
Power consumption	...	max. 240 W
Operation temp	-20 ... 50 °C	-10 °C ... 55 °C
Weight	0.074 kg	3.15 kg
Dimensions	148 x 46 x 16 mm	440 x 300 x 44 mm, RACK 19", 1U
Manufacturer / Brand	BleBox	DAHUA
Guarantee	2 years	5 years