





| | | | | |
|-------------------------------|--|--|---|---|
| | IP VANDALPROOF CAMERA DS-2CD2126G2-ISU(2.8MM)(D) ACUSENSE - 1080p Hikvision | TWILIGHT SENSOR TS-02B7 | CABLE MANAGER TRSH-8- P*P10 | CLEANING STICKS CLEANING-STICKS/20 AG TERMOPASTY |
| |  |  |  |  |
| | 1063.00 PLN 1063.00 PLN | 31.76 PLN 31.76 PLN | 5.60 PLN 5.60 PLN | 22.20 PLN 22.20 PLN |
| Standard | TCP/IP | ... | ... | ... |
| Sensor | 1/2.8" Progressive Scan CMOS | ... | ... | ... |
| Matrix size | 2.1 Mpx | ... | ... | ... |
| In package | ... | ... | 10 pcs The price for package | 20 pcs - The price for package |
| Maximal load | ... | 6 A / 1400 W (resistance load), 350 W (inductive load) | ... | ... |
| Hole diameter | ... | ... | Ø 8 mm | ... |
| Assembly | ... | ... | The bottom layer is equipped with a Scotch tape | ... |
| Application | ... | ... | ... | <ul style="list-style-type: none"> • Cleaning the optics • Cleaning heads in dot matrix printers • Cleaning the mechanical components of printers (including paper feeding mechanisms, print head drives) • LCD displays cleaning • Cleaning keyboards, mice and other electronic equipment with hard-to-reach areas |
| Lighting switching threshold | ... | < 5 Lux ... 50 Lux | ... | ... |
| Material | ... | ... | Plastic | ... |
| Resolution | 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... | ... | ... |
| Lens | 2.8 mm | ... | ... | ... |
| Main features | ... | <ul style="list-style-type: none"> • Length of the cable, 17 cm • For indoor use | ... | ... |
| View angle | 107 ° | ... | ... | ... |
| Range of IR illumination | 30 m | ... | ... | ... |
| RS-485 interface | — | ... | ... | ... |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... | ... | ... |
| Alarm inputs / outputs | 1 / 1 | ... | ... | ... |
| Audio | <ul style="list-style-type: none"> • Microphone built-in, • Audio input • Audio output • Bi-directional audio streaming support • Noise reduction • Compliance with the AAC standard | ... | ... | ... |
| Memory card slot | Micro SD memory cards up to 512GB support (possible local recording) | ... | ... | ... |
| Main stream frame rate | 25 fps @ 2.1 Mpx | ... | ... | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... | ... | ... |
| WEB Server | Built-in | ... | ... | ... |
| Max. number of on-line users | 6 | ... | ... | ... |
| ONVIF | ✓ | ... | ... | ... |
| Mobile phones support | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect | ... | ... | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... | ... | ... |
| Default IP address | 192.168.1.64 | ... | ... | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | |
|----------------------------|---|------------------|---------|-----------------|
| Web browser access ports | 80 | ... | ... | ... |
| PC client access ports | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application | ... | ... | ... |
| Mobile client access ports | 8000 | ... | ... | ... |
| Port ONVIF | 80 | ... | ... | ... |
| RTSP URL | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization | ... | ... | ... |
| Main features | <ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • RESET button • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Sharpness - sharper image outlines • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • Image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection | ... | ... | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA | 220 ... 240 V AC | ... | ... |
| Power consumption | <ul style="list-style-type: none"> • ≤ 6 W @ 12 V DC • ≤ 7.5 W @ PoE (802.3af) | ... | ... | ... |
| Housing | Dome, Metal | Plastic | ... | ... |
| Color | White | ... | Pink | ... |
| "Index of Protection" | IP67 | IP54 | ... | ... |
| Vandal-proof | IK10 | ... | ... | ... |
| Operation temp | -30 °C ... 60 °C | ... | ... | ... |
| Weight | 0.59 kg | 0.048 kg | ... | ... |
| Dimensions | Ø 121 x 92 mm | 75 x 38 x 24 mm | ... | 123 x 12 x 4 mm |
| Supported languages | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian | ... | ... | ... |
| Manufacturer / Brand | Hikvision | ... | ... | AG TERMOPASTY |
| SAP Code | 311319911 | ... | ... | ... |
| Guarantee | 3 years | 2 years | 2 years | ... |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00