





	NVR NVR5464-EI 64 CHANNELS ++eSATA WizSense DAHUA	CAGE NUT ASSEMBLING TOOL SDMK-M5/M6 VALUE	RACK CABINET WALL MOUNT A19-AL	NVR BCS-L-NVR3202-A-4KE(2) 32 CHANNELS BCS Line
				
	10176.60 DKK 10176.60 DKK	28.86 DKK 28.86 DKK	12.81 DKK 12.81 DKK	3415.98 DKK 3415.98 DKK
Holes diameter	10 mm	...
Standard	TCP/IP	TCP/IP
Application	...	M5, M6
Material	...	Aluminum
Supported resolutions	max. 32 Mpx	max. 16 Mpx - 4608 x 3472 px
Video outputs	2 pcs HDMI 4K 2 pcs VGA	1 pcs HDMI 4K 1 pcs VGA
Main features	...	<ul style="list-style-type: none"> • Easy operation • Very easy and quick assembly • Reducing the risk of panel damage • Reduces risk of injury
Color	...	Silver	Black	...
Audio support	<ul style="list-style-type: none"> • 64 Channels - Audio from cameras • Bi-directional audio streaming support 	32 Channels - Audio from cameras
Audio inputs	1 pcs CINCH	1 pcs CINCH
Audio outputs	2 pcs CINCH	1 pcs CINCH
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264 / H.264+ / MJPEG
Bitrate	max. 384 Mbps	max. 256 Mbps
Supported hard drives	4 x 16 TB SATA + 1 x eSATA	2 x 16 TB SATA
Recording modes	Manual, Sensor, Motion detection, Schedule	Manual, Sensor, Motion detection, Schedule
External storage devices backup	Backup to USB drive (pendrive, external drive)	Backup to USB drive (pendrive, external drive)
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 32 channels in the same time @ 1080p (without AI) • Records playback from max. 24 channels in the same time @ 1080p (AI) 	<ul style="list-style-type: none"> Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/9/16 channel synchronous playback
Network interface	2 x RJ-45 10/100/1000 Base-TX	1 x RJ-45 10/100/1000 Base-TX
Network functions	Full support via network, Remote records copying, Web-Server built-in	Full support via network, Remote records copying, Web-Server built-in
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, SNMP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, PPPoE, FTP, DDNS, Alarm Server, IP Search, Multicast, P2P, Auto Register	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register, ONVIF
ONVIF	2.1.12	✓
Default IP address	192.168.1.108	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Mobile phones support	<ul style="list-style-type: none"> Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS <p>See how to configure the P2P function in Dahua recorders and how to enable the mobile application</p>	<ul style="list-style-type: none"> Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Web browser access ports	80, 37777	80, 37777
PC client access ports	37777	37777
Mobile client access ports	37777	37777
RTSP URL	<ul style="list-style-type: none"> rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	<ul style="list-style-type: none"> rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
USB	1 pcs USB 2.0 2 pcs USB 3.0	1 pcs USB 2.0 1 pcs USB 3.0
Serial ports	RS-485, RS-232	-
Alarm inputs / outputs	16 / 6	4 / 2
PTZ control	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others 	IP Speed Dome Cameras
Motion Detection	✓	✓
Intelligent image analysis	✓	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> Intelligent image analysis : crossing the line (tripwire), intrusion, face detection SMD PLUS - searching for an object classified as: human, motor vehicle Filtering of false alarms based on the recognition of persons and vehicles Face recognition Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) Support for up to 20 face databases, including 20 000 face images In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity Privacy zones Cooperation with POS (Point of Sale) terminals <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> ANPR Authorized and unauthorized license plate lists: up to 20 000 records counting people / vehicles crowd gathering estimation heat map metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) 	<ul style="list-style-type: none"> Intelligent image analysis : 10 rules, face detection - supports 6 types of facial attributes extraction Face recognition Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) Support for up to 10 face databases, including 20 000 face images SMD PLUS - searching for an object classified as: human, motor vehicle <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> face detection Face recognition SMD PLUS - searching for an object classified as: human, motor vehicle Filtering of false alarms based on the recognition of persons and vehicles ANPR people counting heat map
Mouse support	✓	✓
IR remote controller in the set	—	—
Power supply	100 ... 240 V AC @ 50 / 60 Hz	12 V DC / 4 A (power adapter included)
Power consumption	max. 13 W (without HDD)	max. 10 W (without HDD)
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	4.44 kg	0.025 kg	0.25 kg	1.5 kg
Dimensions	440 x 415 x 76 mm	75 x 40 x 14 mm	...	375 x 282 x 53 mm
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian	Polish, English
Manufacturer / Brand	DAHUA	VALUE	...	BCS Line
Guarantee	3 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00