



	<a href="#">CONTACTS CLEANING PREPARATION KONTAKT-S/400 SPRAY 400 ml AG TERMOPASTY</a>	<a href="#">SWITCH POE CS4010-8GT-110 8-PORT DAHUA</a>
		
	27.86 PLN 27.86 PLN	1124.00 PLN 1124.00 PLN
Package	Spray 400 ml	...
Application	Cleaning and regeneration of contacts	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 8 x RJ45 10/100/1000 Base-T ( 1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink</li> </ul>
Transmission speed	...	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 8 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 : 2 Uplink ports</li> </ul>
Maximal output power	...	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE / PoE 802.3bt - Port 1</li> <li>• 30 W / port PoE 802.3af/at - 2 ... 8 ports</li> </ul>
Maximal total power	...	110 W
MAC addresses table	...	8k
Management	...	✓
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes	...	Power, System, PoE, Link/Act

Main features	Spray preparation with a brush for easy application in hard-to-reach places	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLynk Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Spanning Tree STP/RSTP</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Possibility to mount to the wall</li> </ul>
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> <li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>
Housing	...	Desktop, Metal
Power supply	...	54 V DC / 2.22 A (power adapter included)
Power consumption	...	max. 110 W
Operation temp	...	-10 °C ... 55 °C
Weight	0.36 kg	0.52 kg
Dimensions	Ø 66 x 187 mm	190 x 106 x 30 mm
Manufacturer / Brand	AG TERMOPASTY	DAHUA
Guarantee	...	3 years