



	HEX HEAD SCREW SS-M8X40/KL-8.8	IP CAMERA IPC-HFW1230S-0360B-S5 - 1080p 3.6 mm DAHUA
		
	0.85 PLN 0.85 PLN	481.00 PLN 481.00 PLN
Standard	...	TCP/IP
Size	M8	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Material	Steel galvanized	...
Strength class	8.8	...
Matrix size	...	2.1 Mpx
Main features	DIN 933 compliance	...
Scanning system	...	Progressive
Wrench size	13 mm	...
Thread length	40 mm	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	3.6 mm
View angle	...	<ul style="list-style-type: none"> • 84 ° (manufacturer data) • 82 ° (our tests result)
Range of IR illumination	...	30 m
RS-485 interface	...	—
Memory card slot	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	—
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, NTP, Multicast
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	19.12
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image • Configurable Privacy Zones • Motion Detection
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 360 mA
Power consumption	...	<ul style="list-style-type: none"> ≤ 4.3 W @ 12 V DC ≤ 5.5 W @ PoE
Housing	...	Compact - Metal
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	0.017 kg	0.4 kg
Dimensions	...	Ø 70 x 165 mm
Supported languages	...	English, Spanish, Russian
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years

