




	MOUNTING SCREWS SM-6/RACK-B	PANEL WITH CABLE ENTRY A19-PK-V1	POWER DISTRIBUTION UNIT ACAR-SMART (6 OUTLETS)
			
	2.00 PLN 2.00 PLN	22.40 PLN 22.40 PLN	91.60 PLN 91.60 PLN
Width	...	19 "	...
Rated voltage	230 V AC / 50 Hz
Height	...	1 U	...
Protection level	≤ 1.3 kV
Nominal load current	10 A (total)
Color	...	Black (RAL 9005)	...
Application	Rack 19" / Rack 10"	RACK 19"	...
Maximum stroke current	6.5 kA (L/N)
Package includes	<ul style="list-style-type: none"> • 4 x M6 screw, Torx T-25 socket, • 4 x cage nut, • 4 x plastic shoulder washer, which protects the varnish coating of panels from damage during tightening the screws
Nominal stroke current	2 kA (L/N) 8/20 μs 8/20 μs
Leak current	< 0.5 mA
Response time	< 25 ns
Material	Steel, Anodized surface	Steel - powder painted	...
Main features	...	<ul style="list-style-type: none"> • Dimensions of the cable entry hole : 431 x 27 mm (full frame) • 4-point fixing to the front RACK rails • 4 pcs. of M6 screws with cage nuts included • Corrosion resistance 	...
Number of output outlets	6
Switch	2 pcs
Length of the cable	1.4 m
Housing	Plastic - non-flammable
Dimensions	...	483 x 44 x 12 mm	138 x 100 x 63 mm
Weight	0.035 kg	0.25 kg	0.4 kg
Guarantee	2 years	2 years	2 years